
PHILIPS

Lighting



Core & Coil (71A) MH ~GT~ 450W

CORE & COIL HID MH BAL 750W M149 347/480V/120T C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information	
ANSI Code	M149
Lamp Type	750W MH
Number of Lamps	1 piece/unit
Circuit Type	SUPER-CWA
Ballast Type	Magnetic HID
Base Model	71A64F0T
Core Size	4 1/4 x 4 3/4 (2 coil)
Suitable For Outdoor Use	Yes
Ignitor Catalog Number	LI573-H5
Ignitor Temperature Rating	105°C
Capacitor Value	28 MFD
Capacitor Catalog Number	7C280S40
Capacitor Requirements	400V
Capacitor Temperature Rating	105°C
Capacitor Diameter/Oval Dimensions	2 in
Capacitor Height	4.8 in
Automatic Restart	No

Operating and Electrical	
Input Voltage	347/480/120T V
Input Frequency	60 Hz
Inp. Current (Open Circuit)	1.35/1 A
Input Current (Starting)	1.8/1.4 A
Input Current (Short Circuit)	1.45-2.15/1.1-1.65 V
Secondary Short Circuit Current	4.9-6 A
Constant Wattage Deviation	10%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Nominal Open Circuit Voltage	340 V
Input Current (Operating) (Nom)	2.5/1.75 A A
Input Power (Nom)	820 W
Rated Lamp Watts	750 W

Wiring	
Wire Striplength	0.5 mm
Wire Length by Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes

Core & Coil (71A) MH ~GT~ 450W

Max Ballast-Lamp Distance Remote Wiring	15'
Recommended Fuse Value	6/4 A


Approval and Application

Open Circuit Voltage Test (Volts)	306-375 V
Approbation Marks	ULR CSA certificate RoHS Compliant
Temperature Marking	A/A
UL Recognized	Yes
Hipot Test (1 Minute)	1500 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	N(AC200°C)
UL Temperature Code	1029A

Product Data

Order product name	CORE & COIL HID MH BAL 750W M149 347/480V/120T C&C
EAN/UPC - Product	781087044131
Order code	71A64F0600T
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	3
Material Nr. (12NC)	913710582002
Net Weight (Piece)	6.428 kg

Dimensional drawing



MH BAL 750W M149 347/480V/120T C&C

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A64F0600T	4.9 in	3 in	4.8 in	4.4 in	4.3 in	3.9 in

© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.