



# Core & Coil (71A) MH ~GT~ 450W

## CORE & COIL HID MH BAL 750W M149 277/347/480V KIT

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

#### **Product data**

General Information					
ANSI Code	M149				
Lamp Type	750W MH				
Number of Lamps	1 piece/unit				
Circuit Type	SUPER-CWA				
Ballast Type	Magnetic HID				
Base Model	71A64F2				
Core Size	4 1/4 x 6 (2 Coil)				
Suitable For Outdoor Use	Yes				
Ignitor Catalog Number	LI573-H5				
Ignitor Temperature Rating	105°C				
Capacitor Value	28 MFD				
Capacitor Catalog Number	7C280S40				
Capacitor Requirements	400V				
Capacitor Temperature Rating	105°C				
Capacitor Diameter/Oval Dimensions	2 in				
Capacitor Height	4.80 in				
Automatic Restart	No				

Operating and Electrical				
Input Voltage	277/34/480 V			
Input Frequency	60 Hz			
Input Current (Open Circuit)	1.8/1.45/1 A			
Input Current (Starting)	2.2/1.65/1.25 A			
Input Current (Short Circuit)	1.7-2.6/1.35-2.05/1-1.5 V			
Secondary Short Circuit Current	5-6 A			
Constant Wattage Deviation	10%			
Ballast Factor (Nom)	1			
Power Factor (Nom)	0.90			
Open Circuit Voltage	355 V			
Input Current (Nom)	3/2.45/1.75 A A			
Input Power (Nom)	818 W			
Rated Lamp Power	750 W			
Wiring				
Wire Striplength	0.5 mm			
Wire Length by Color	12"			
Wire Type	Stranded			
Remote Wiring Configuration Allowed	Yes			


Datasheet, 2019, March 22 data subject to change

### Core & Coil (71A) MH ~GT~ 450W

Max Ballast-Lamp Distance Remote Wiring 15'					
Recommended Fuse Value	8/7/5 A				
Approval and Application					
Open Circuit Voltage Test (Volts)	320-390 V				
Approval Marks	ULR CSA certificate RoHS Compliant				
Temperature Marking	E/E/E				
UL Recognized	Yes				
Hipot Test (1 Minute)	2000 V				
Hipot Test (2 Seconds)	2500 V				
UL Insulation Class	H(180°C)				
UL Temperature Code	1029E				

Product Data				
Order product name	CORE & COIL HID MH BAL 750W M149			
	277/347/480V KIT			
EAN/UPC - Product	781087052198			
Order code	199752			
Local order code	199752			
Numerator - Quantity Per Pack	1			
Numerator - Packs per outer box	1			
Material Nr. (12NC)	913710605001			
Net Weight (Piece)	8.587 kg			

#### Dimensional drawing



MH BAL 750W M149 277/347/480V KIT

Product	C1	C2	A1	A2	А3	B1	B2
CORE & COIL HID MH BAL 750W	4.25 in	2.28 in	6 in	5.4 in	4.4 in	4.3 in	3.9 in
M149 277/347/480V KIT							

