



Core & Coil (71A) MH ~GT~ 450W

CORE & COIL HID MH BAL 1000W M47 QUAD C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information					
ANSI Code	M47				
Lamp Type	1000W MH				
Number of Lamps	1 piece/unit				
Circuit Type	CWA				
Ballast Type	Magnetic HID				
Base Model	71A6592				
Core Size	4 1/4 x 6 (2 Coil)				
Suitable For Outdoor Use	Yes				
Ignitor Catalog Number	NA				
Ignitor Temperature Rating	NA				
Capacitor Value	24 MFD				
Capacitor Catalog Number	MD2409000				
Capacitor Requirements	480V				
Capacitor Temperature Rating	90°C				
Capacitor Diameter/Oval Dimensions	1.75 in				
Capacitor Height	3.90 in				
Automatic Restart	No				
Operating and Electrical					
Input Voltage	120/208/240/277 V				

Input Frequency	60 Hz
Input Current (Open Circuit)	4.5/2.7/2.3/2.2 A
Input Current (Starting)	7.8/4/3.7/3.2 A
Input Current (Short Circuit)	5.6-8.6/3.2-4.8/2.8-4.3/2.4-3.6 V
Secondary Short Circuit Current	5.2-6.4 A
Constant Wattage Deviation	10%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Open Circuit Voltage	430 V
Input Current (Nom)	9/5.2/4.5/3.9 A A
Input Power (Nom)	1080 W
Rated Lamp Power	1000 W
Wiring	
Wire Striplength	0.5 mm
Wire Length by Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes
Max Ballast-Lamp Distance Remote	Determined by AWG used
Wiring	


Datasheet, 2019, March 22 data subject to change

Core & Coil (71A) MH ~GT~ 450W

Recommended Fuse Value	20/15/10/10 A					
Approval and Application						
Open Circuit Voltage Test (Volts)	385-475 V					
Approval Marks	ULR CSA certificate RoHS Compliant					
Temperature Marking	A/A/A/A					
UL Recognized	Yes					
Hipot Test (1 Minute)	2000 V					
Hipot Test (2 Seconds)	2500 V					
UL Insulation Class	N(AC200°C)					
UL Temperature Code	1029A					

Product Data					
Order product name	CORE & COIL HID MH BAL 1000W M47 QUAD				
	C&C				
EAN/UPC - Product	781087022665				
Order code	913710614502				
Numerator - Quantity Per Pack	1				
Numerator - Packs per outer box	2				
Material Nr. (12NC)	913710614502				
Net Weight (Piece)	9.612 kg				

Dimensional drawing



MH BAL 1000W M47 QUAD C&C

Product	C1	C2	A1	A2	А3	B1	B2
CORE & COIL HID MH BAL 1000W	4.5 in	2.57 in	6 in	5.4 in	4.4 in	4.3 in	3.9 in
M47 QUAD C&C							

