



## Val-U-Pak Plus (77L)

# CORE & COIL HID MH BAL 100W M90/140 QUAD KIT WITH LAMP

Our VAL-U-PAK Plus magnetic HID replacement kits assemble the required components — including lamp, core and coil, the appropriate capacitor, ignitor (where required), mounting bracket and hardware, and instructions — in one convenient package. This saves valuable time for MRO and contractor applications.

#### **Product data**

General Information	
ANSI Code	M90-M140
Lamp Type	100 MH
Number of Lamps	1 piece/unit
Circuit Type	HX-HPF
Ballast Type	Magnetic HID
Base Model	71A5390
Core Size	3 X 4 (2 LW)
Suitable For Outdoor Use	Yes
Ignitor Catalog Number	LI533-H4
Ignitor Temperature Rating	105°C
Capacitor Value	12 MFD
Capacitor Catalog Number	7C120M30RA
Capacitor Requirements	280V
Capacitor Temperature Rating	105°C
Capacitor Diameter/Oval	1.65 in
Dimensions	
Capacitor Height	2.75 in
Automatic Restart	No
Operating and Electrical	
Input Voltage	120/208/240/277 V

Input Current (Open Circuit)         2.5/1.5/1.3/1.12 A           Input Current (Starting)         1.24/0.54/0.45/0.4 A           Input Current (Short Circuit)         0.63-0.95/0.43-0.65/0.37-0.55/0.29-0.44 A           Secondary Short Circuit Current         1.35-1.7 A           Constant Wattage Deviation         12%           Ballast Factor (Nom)         1           Power Factor (Nom)         0.90           Open Circuit Voltage         260 V           Input Current (Nom)         1.15/0.66/0.58/0.5 A A	Input Frequency	60 Hz				
Input Current (Short Circuit)         0.63-0.95/0.43-0.65/0.37-0.55/0.29-0.44 A           Secondary Short Circuit Current         1.35-1.7 A           Constant Wattage Deviation         12%           Ballast Factor (Nom)         1           Power Factor (Nom)         0.90           Open Circuit Voltage         260 V           Input Current (Nom)         1.15/0.66/0.58/0.5 A A	Input Current (Open Circuit)	2.5/1.5/1.3/1.12 A				
Secondary Short Circuit Current 1.35-1.7 A  Constant Wattage Deviation 12%  Ballast Factor (Nom) 1  Power Factor (Nom) 0.90  Open Circuit Voltage 260 V  Input Current (Nom) 1.15/0.66/0.58/0.5 A A	Input Current (Starting)	1.24/0.54/0.45/0.4 A				
Constant Wattage Deviation         12%           Ballast Factor (Nom)         1           Power Factor (Nom)         0.90           Open Circuit Voltage         260 V           Input Current (Nom)         1.15/0.66/0.58/0.5 A A	Input Current (Short Circuit)	0.63-0.95/0.43-0.65/0.37-0.55/0.29-0.44 A				
Ballast Factor (Nom)         1           Power Factor (Nom)         0.90           Open Circuit Voltage         260 V           Input Current (Nom)         1.15/0.66/0.58/0.5 A A	Secondary Short Circuit Current	1.35-1.7 A				
Power Factor (Nom)         0.90           Open Circuit Voltage         260 V           Input Current (Nom)         1.15/0.66/0.58/0.5 A A	Constant Wattage Deviation	12%				
Open Circuit Voltage         260 V           Input Current (Nom)         1.15/0.66/0.58/0.5 A A	Ballast Factor (Nom)	1				
Input Current (Nom) 1.15/0.66/0.58/0.5 A A	Power Factor (Nom)	0.90				
	Open Circuit Voltage	260 V				
	Input Current (Nom)	1.15/0.66/0.58/0.5 A A				
Input Power (Nom) 129 W	Input Power (Nom)	129 W				
Rated Lamp Power 100 W	Rated Lamp Power	100 W				
Wiring	Wiring					
Wire Striplength 0.5 mm	Wire Striplength	0.5 mm				
Wire Length by Color 12"	Wire Length by Color	12"				
Wire Type Stranded	Wire Type	Stranded				
Remote Wiring Configuration Yes	Remote Wiring Configuration	Yes				
Allowed	Allowed					
Max Ballast-Lamp Distance 20'	Max Ballast-Lamp Distance	20'				
Remote Wiring	Remote Wiring					


Datasheet, 2019, February 12 data subject to change

### Val-U-Pak Plus (77L)

Recommended Fuse Value	10/5/5/4 A
Approval and Application	
Open Circuit Voltage Test	240-300 V
(Volts)	
Approval Marks	ULR CSA certificate RoHS Compliant
Temperature Marking	B/B/A/A
UL Recognized	Yes
Hipot Test (1 Minute)	2000 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)
UL Temperature Code	1029B

Product Data	
Order product name	CORE & COIL HID MH BAL 100W M90/140 QUAD KIT
	WITH LAMP
EAN/UPC - Product	781087068175
Order code	913710661301
Numerator - Quantity Per Pack	1
Numerator - Packs per outer	1
box	
Material Nr. (12NC)	913710661301
Net Weight (Piece)	3.443 kg

### Dimensional drawing



MH BAL 100W M90/140 QUAD KIT

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 77L5390001D	3.07 in	1.5 in	3.9 in	3.5 in	2.8 in	2.4 in

