



Core & Coil (71A) MH 175W - 450W

CORE & COIL HID MH BAL 320W M132/M154 480V/120T C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information	
ANSI Code	M132-M154
Lamp Type	320W MH
Number of Lamps	1 piece/unit
Circuit Type	SUPER-CWA
Ballast Type	Magnetic HID
Base Model	71A5842TAEE
Core Size	4 1/4 x 4 3/4 (2 coil)
Suitable For Outdoor Use	Yes
Ignitor Catalog Number	LI533-H4
Ignitor Temperature Rating	105°C
Capacitor Value	21 MFD
Capacitor Catalog Number	7C210P40R
Capacitor Requirements	345V
Capacitor Temperature Rating	105°C
Capacitor Diameter/Oval Dimensions	1.75 in
Capacitor Height	4.80 in
Automatic Restart	No

Operating and Electrical	
Input Voltage	480/120T V
Input Frequency	60 Hz
Inp. Current (Open Circuit)	0.53 A
Input Current (Starting)	0.58 A
Input Current (Short Circuit)	0.46-0.70 A
Secondary Short Circuit Current	2.8-3.5 A
Constant Wattage Deviation	10%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Nominal Open Circuit Voltage	285 V
Input Current (Operating) (Nom)	0.8 A A
Input Power (Nom)	363 W
Rated Lamp Watts	320 W
Wiring	
Wire Striplength	0.5 mm
Wire Length by Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes


Datasheet, 2019, February 12 data subject to change

Core & Coil (71A) MH 175W - 450W

Max Ballast-Lamp Distance Remote Wiring	2'
Recommended Fuse Value	3 A
Approval and Application	
Open Circuit Voltage Test (Volts)	260-310 V
Approbation Marks	ULR CSA certificate EISA RoHS Compliant
Temperature Marking	А
UL Recognized	Yes
Hipot Test (1 Minute)	2000 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)
UL Temperature Code	1029A

Product Data	
Order product name	CORE & COIL HID 71A5842500DTAEE
EAN/UPC - Product	781087070383
Order code	71A5842500DTAEE
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	913710665702
Net Weight (Piece)	5.648 kg

Dimensional drawing



MH BAL 320W M132/M154 480V/120T C&C

 Product
 C1
 C2
 A1
 A2
 B1
 B2

 CORE & COIL HID 71A5842500DTAEE
 4.10 in
 2.20 in
 4.8 in
 4.4 in
 4.3 in
 3.9 in



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.