
PHILIPS

Lighting



Core & Coil (71A) MH 175W - 450W

CORE & COIL HID 71A5792600EE

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information	
ANSI Code	M138-M153
Lamp Type	250W MH
Number of Lamps	1 piece/unit
Circuit Type	SUPER-CWA
Ballast Type	Magnetic HID
Base Model	71A5792EE
Core Size	4 1/4 x 4 3/4 (2 coil)
Suitable For Outdoor Use	Yes
Ignitor Catalog Number	LI533-H4
Ignitor Temperature Rating	105°C
Capacitor Value	17 MFD
Capacitor Catalog Number	7C170P40
Capacitor Requirements	330V
Capacitor Temperature Rating	105°C
Capacitor Diameter/Oval Dimensions	1.75 in
Capacitor Height	3.75 in
Automatic Restart	No

Operating and Electrical	
Input Voltage	120/208/240/277 V
Input Frequency	60 Hz
Input Current (Open Circuit)	1.1/0.64/0.55/0.48 A
Input Current (Starting)	2.27/1.34/1.13/0.98 A
Input Current (Short Circuit)	1.79-2.68/1.03-1.59/0.89-1.34/0.77-1.16 A
Secondary Short Circuit Current	2.42-2.96 A
Constant Wattage Deviation	10%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Open Circuit Voltage	280 V
Input Current (Nom)	2.52/1.44/1.26/1.1 A A
Input Power (Nom)	291 W
Rated Lamp Power	250 W


Wiring	
Wire Striplength	0.5 mm
Wire Length by Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes
Max Ballast-Lamp Distance Remote Wiring	2'
Recommended Fuse Value	8/5/5/3 A

Core & Coil (71A) MH 175W - 450W

Approval and Application	
Open Circuit Voltage Test (Volts)	254-308 V
Approval Marks	ULR CSA certificate EISA RoHS Compliant
Temperature Marking	A/A/A/A
UL Recognized	Yes
Hipot Test (1 Minute)	1500 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)
UL Temperature Code	1029A

Product Data	
Order product name	CORE & COIL HID 71A5792600EE
EAN/UPC - Product	781087076118
Order code	913710678702
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	913710678702
Net Weight (Piece)	4.786 kg

Dimensional drawing



MH BAL 250W M138/M153 QUAD C&C

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A5792600EE	3.55 in	1.61 in	4.8 in	4.4 in	4.3 in	3.9 in

© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.