



# PrimaVision Economy for CDM lamps

## HID-PV E 35 /S CDM 220-240V

Single CDM lamp operation, single HID electronic gear – improves cost effectiveness and increases luminaire design flexibility

### Product data

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Earth Leakage Current (Max)	0.5 mA
Inrush Current Width	0.25 ms
Input Current (Nom)	0.2 A
Inrush Current Peak (Max)	26 A
Wiring	
Cable Length From Device to Lamp	2 m
Connector Type	WAGO 235
Temperature	
Ambient temperature range	-20 °C to 55 °C
T-Case Lifetime (Nom)	80 °C
Mechanical and Housing	
Housing	/S

Approval and Application	
Surge Protection (Common/Differential)	EN61547 (L-L 1kV, L-G 2kV) kV
Safety Standard	IEC 61347-2-11
Environmental Standard	ISO 14001
Approval Marks	CE marking ENEC certificate VDE-EMV certificate
Product Data	
Full product code	694793917422500
Order product name	HID-PV E 35 /S CDM 220-240V
Order code	913712006880
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	913712006880
Full product name	HID-PV E 35 /S CDM 220-240V
EAN/UPC - Case	6947939174232
EAN/UPC - Product/Case	6947939174225

## PrimaVision Economy for CDM lamps

### Dimensional drawing

Product	D1	C1	A1	A2	B1	B2
HID-PV E 35 /S CDM 220-240V	4 mm	31.6 mm	109.8 mm	98.7 mm	74.8 mm	63.7 mm

