



HID-PV/DV economy for CPO-CDM

HID-CV 210 /S CPO - CDM 220-240V 50/60HZ

Certavision driver is an electronic driver for CPO or CDM Elite MW lamps – helps create an efficient white-light system.

Product data


Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Factor 50% Load (Min)	0.95
Earth Leakage Current (Max)	0.7 mA
Inrush Current Width	700 ms
Inrush Current Peak (Max)	65 A
Wiring	
Cable Length From Device to Lamp	1.5 m
Connector Type	WAGO series 804
Temperature	
Ambient temperature range	-20 °C to 50 °C
T-Case Lifetime (Nom)	80 ℃
Mechanical and Housing	
Housing	C2

Approval and Application		
Surge Protection (Common/Differential) EN61547 kV		
Safety Standard	IEC 61347-2-11	
Environmental Standard	ISO 14001	
Approval Marks	CE marking China Quality Certificate KEUR	
Product Data		
Order product name	HID-CV 210 /S CPO - CDM 220-240V 50/60HZ	
Full product name	HID-CV 210 /S CPO - CDM 220-240V 50/60HZ	
Full product code	694793917426300	
Order code	913712008070	
Material Nr. (12NC)	913712008070	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	6947939174263	
Numerator - Packs per outer box	6	
EAN/UPC - Case	6947939174270	

Datasheet, 2023, April 17 data subject to change

HID-PV/DV economy for CPO-CDM

Dimensional drawing



 Product
 D1
 C1
 A1
 A2
 B1
 B2

 HID-CV 210 /S CPO - CDM
 4.8 mm
 58.0 mm
 168.1 mm
 156.4 mm
 100.0 mm
 81.5 mm

 220-240V 50/60HZ



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.