



EB-Certalume for TL5 lamps

EB-C 128 TL5 220-240V 50/60Hz

Affordable, reliable, high frequency electronic ballast for TL5 fluorescent lamps, ideal alternative for electromagnetic (EM) ballasts

Product data


Operating and Electrical				
Input Voltage	220 to 240 V			
Line Frequency	50 to 60 Hz			
Input Frequency	50 to 60 Hz			
Earth Leakage Current (Max)	0.7 mA			
Wiring				
Connector Type Input Terminals	250 manual connector [Suitable for manual wiring			
	and easy release button]			
Color Input Terminals	Orange			
Color Output Terminals	Grey			
Connector Type Output Terminals	250 manual connector [Suitable for manual wiring			
	and easy release button]			
Temperature				
T-Case Lifetime (Nom)	75 ℃			
Mechanical and Housing				
Housing	L 275x20x21			

Approval and Application			
Ingress protection code	IP20 [Finger-protected]		
Energy Efficiency Index	A2		
Approval Marks	CCC certificate CB Certificate		
Product Data			
Order product name	EB-C 128 TL5 220-240V 50/60Hz		
Full product name	EB-C 128 TL5 220-240V 50/60Hz		
Full product code	872790088656600		
Order code	88656600		
Material Nr. (12NC)	913713196414		
Numerator - Quantity Per Pack	1		
EAN/UPC - Product/Case	8711500998927		
Numerator - Packs per outer box	50		
EAN/UPC - Case	8727900886566		

Datasheet, 2023, April 17 data subject to change

EB-Certalume for TL5 lamps

Dimensional drawing



Product	D1	C1	A1	A2	B1
EB-C 128 TL5 220-240V 50/60Hz	4.2 mm	21.0 mm	275.0 mm	265.0 mm	19.8 mm

