



Copenhagen LED Big

BRS441 ECO127-3S/740 II DP-R GR T25 C10K

Big Copenhagen LED side entry, LED EconomyLine 12700 lm, 740 neutral white, Safety class II, Distribution pedestrian crossing right, Flat glass, Cable 10 m without plug

Copenhagen LED was co-designed together with Copenhagen’s Office of City Architecture in order to enhance the aesthetic appeal of the city’s lighting. The luminaire’s timeless design comes in two sizes – mini and large – to ensure that the dimensions of the luminaire and pole are well balanced, and that the installation blends in harmoniously with its surroundings. A variety of suspensions are available, offering maximum freedom in the overall design of the installation. A choice of symmetrical or asymmetrical distributions and state-of-the-art LED technology complete the specification of an extremely adaptable luminaire.

Product data

General Information		Lighting Technology	
Lamp family code	ECO127 [LED EconomyLine 12700 lm]	Embedded control	-
Light source replaceable	Yes	CE mark	Yes
Number of gear units	1 unit	Warranty period	5 years
Driver included	Yes	Flammability mark	For mounting on normally flammable surfaces
Remarks	*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore, the median useful life (B50) value also represents the B10 value.	ENEC mark	-
Light source engine type	LED	EU RoHS compliant	Yes
Product family code	BRS441 [Big Copenhagen LED side entry]	Light Technical	
		Upward light output ratio	0
		Luminous Flux	10,640 lumen
		Standard tilt angle posttop	0°
		Standard tilt angle side entry	0°

Copenhagen LED Big

Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	11 lm/W
Color rendering index (CRI)	≥70
Number of light sources	1
Light source color	740 neutral white
Optical cover type	Flat glass
Luminaire light beam spread	180°
Optic type outdoor	Distribution pedestrian crossing right

Operating and Electrical

Input Voltage	220/240 V
Line Frequency	50 to 60 Hz
Inrush current	53 A
Inrush time	0.30 ms
Power Consumption	105 W
Power Factor (Fraction)	0.9
Connection	-
Cable	Cable 10 m without plug
Number of products on MCB of 16 A type B	8

Temperature

Ambient temperature range	-40 to +50 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit regulating
Control interface	-
Constant light output	No

Mechanical and Housing

Reflector material	-
Optic material	Polycarbonate
Optical cover material	Glass
Fixation material	Aluminum
Housing Color	Gray
Mounting device	Side-entry for diameter 48 mm
Optical cover shape	Flat
Optical cover finish	Clear

Overall height	367 mm
Overall diameter	462 mm
Effective projected area	0.13 m²

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Surge Protection (Common/Differential)	Luminaire surge protection level until 6 kV differential mode and 8 kV common mode
Protection class IEC	Safety class II

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-7%
Initial chromaticity	(0.382, 0.380) SDCM <5
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 100000 h	10 %
Lumen maintenance at median useful life* 100000 h	L80

Application Conditions

Performance ambient temperature Tq	25 °C
------------------------------------	-------

Product Data

Full product code	871829198936300
Order product name	BRS441 ECO127-3S/740 II DP-R GR T25 C10K
Order code	919008632343
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	919008632343
Full product name	BRS441 ECO127-3S/740 II DP-R GR T25 C10K
EAN/UPC - Case	8718291989363
EAN/UPC - Product/Case	8718291989363

Copenhagen LED Big

Dimensional drawing

