



Greenled I

189/190/191/192/193/ 194/195 downlight

DN194B LED15S-3000 PSU WH S1

GreenLed I family is general purpose High performance Led downlight family suitable for use in a series of lighting applications in Office, Retail and General Area Lighting . Available in a wide variety of lumen packs & color temp.

Warnings and Safety

- Meant for use in Indoor environment only

Product data

Light Technical	
Correlated Color Temperature (Nom)	3000 K
Color rendering index (CRI)	>80
Light source color	830 warm white
Luminaire light beam spread	110°
Operating and Electrical	
Input Voltage	220-240 V
Line Frequency	50 Hz
Input Frequency	50 Hz
Power Consumption	15 W
Power Factor (Fraction)	0.9
Temperature	
Ambient temperature range	0 to +45 °C

Controls and Dimming	
Dimmable	No
Control interface	-
Mechanical and Housing	
Housing Material	Aluminum die cast
Housing Color	White
Overall height	100 mm
Overall diameter	185 mm
Material	Aluminum
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Surge Protection (Common/Differential)	2.5 kV

Greenled I 189/190/191/192/193/194/195 downlight

Protection class IEC	Safety class I
Initial Performance (IEC Compliant)	
Power consumption tolerance	+/-10%
Product Data	
Order product name	DN194B LED15S-3000 PSU WH S1

Full product name	DN194B LED15S-3000 PSU WH S1
Order code	919515810384
Material Nr. (12NC)	919515810384
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	8

Dimensional drawing

Product: GreenLED I
Type: DN189B/ DN 190B/ DN 191B/ DN 192B/ DN193B/ DN 194B/ DN195B
Application: Indoor

