



# Standard Extra Low Voltage A60

# Stan ELV 60W E27/BRC 50V A60 CL 1CT

Clear lamp (A-bulb) for operation on voltages of 12, 24, 42 and 50  $\rm V$ 

### **Product data**


General Information	
Cap-Base	E27
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal lifetime	1,000 hour(s)
Switching Cycle	4,000
Rated Lifetime (Hours)	1,000 hour(s)
Lighting Technology	Incandescent
Light Technical	
Luminous Flux	810 lm
Correlated Color Temperature (Nom)	2700 K
Color rendering index (CRI)	100
Operating and Electrical	
Power Consumption	60.0 W
Starting Time (Nom)	0.0 s
Warm-up time to 60% light	instant full light s
Voltage (Nom)	50 V
Voltage (Nom)	50 V
Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	A60
Approval and Application	
Energy Consumption kWh/1000 h	60 kWh
Product Data	
Order product name	Stan ELV 60W E27/BRC 50V A60 CL 1CT
Full product name	Stan ELV 60W E27/BRC 50V A60 CL 1CT
Full product code	871150010188484
Order code	920021025303
Material Nr. (12NC)	920021025303
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500101884
Numerator - Packs per outer box	120
EAN/UPC - Case	8711500348999
	·

Datasheet, 2024, February 26 data subject to change

## Standard Extra Low Voltage A60

### Dimensional drawing



Product	D (max)	C (max)
Stan ELV 60W E27/BRC 50V A60 CL 1CT	60 mm	107.5 mm



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.