



Standard Lustre P45 clear

Stan 25W E14 230V P45 CL 1CT/10X10F

Spherical vacuum- or gas-filled incandescent lamps with a clear glass bulb and E-or B-base

Product data


General Information Cap-Base E14 [E14] Operating Position UNIVERSAL [Any or Universal (U)] Nominal lifetime 1,000 hour(s) Rated Lifetime (Hours) 1,000 hour(s) Lighting Technology Incandescent Light Technical Luminous Flux 215 lm Color rendering index (CRI) 100 Operating and Electrical Power Consumption 25 W Voltage (Nom) 230 V Controls and Dimming Dimmable Yes		
Operating Position UNIVERSAL [Any or Universal (U)] Nominal lifetime 1,000 hour(s) Rated Lifetime (Hours) 1,000 hour(s) Lighting Technology Incandescent Light Technical Luminous Flux 215 lm Color rendering index (CRI) 100 Operating and Electrical Power Consumption 25 W Voltage (Nom) 230 V Controls and Dimming	General Information	
Nominal lifetime 1,000 hour(s) Rated Lifetime (Hours) 1,000 hour(s) Lighting Technology Incandescent Light Technical Luminous Flux 215 lm Color rendering index (CRI) 100 Operating and Electrical Power Consumption 25 W Voltage (Nom) 230 V Voltage (Nom) 230 V Controls and Dimming	Cap-Base	E14 [E14]
Rated Lifetime (Hours) Lighting Technology Incandescent Light Technical Luminous Flux Color rendering index (CRI) Operating and Electrical Power Consumption 25 W Voltage (Nom) 230 V Voltage (Nom) 230 V Controls and Dimming	Operating Position	UNIVERSAL [Any or Universal (U)]
Lighting Technology Incandescent Light Technical Luminous Flux 215 lm Color rendering index (CRI) 100 Operating and Electrical Power Consumption 25 W Voltage (Nom) 230 V Voltage (Nom) 230 V Controls and Dimming	Nominal lifetime	1,000 hour(s)
Light Technical Luminous Flux 215 lm Color rendering index (CRI) 100 Operating and Electrical Power Consumption 25 W Voltage (Nom) 230 V Voltage (Nom) 230 V Controls and Dimming	Rated Lifetime (Hours)	1,000 hour(s)
Luminous Flux 215 lm Color rendering index (CRI) 100 Operating and Electrical Power Consumption 25 W Voltage (Nom) 230 V Voltage (Nom) 230 V Controls and Dimming	Lighting Technology	Incandescent
Luminous Flux 215 lm Color rendering index (CRI) 100 Operating and Electrical Power Consumption 25 W Voltage (Nom) 230 V Voltage (Nom) 230 V Controls and Dimming		
Color rendering index (CRI) 100 Operating and Electrical Power Consumption 25 W Voltage (Nom) 230 V Voltage (Nom) 230 V Controls and Dimming	Light Technical	
Operating and Electrical Power Consumption 25 W Voltage (Nom) 230 V Voltage (Nom) 230 V Controls and Dimming	Luminous Flux	215 lm
Power Consumption 25 W Voltage (Nom) 230 V Voltage (Nom) 230 V	Color rendering index (CRI)	100
Power Consumption 25 W Voltage (Nom) 230 V Voltage (Nom) 230 V		
Voltage (Nom) 230 V Voltage (Nom) 230 V Controls and Dimming	Operating and Electrical	
Voltage (Nom) 230 V Controls and Dimming	Power Consumption	25 W
Controls and Dimming	Voltage (Nom)	230 V
	Voltage (Nom)	230 V
Dimmable Yes	Controls and Dimming	
	Dimmable	Yes

Mechanical and Housing		
Bulb Finish	Clear	
Bulb Shape	P45 [P 45mm]	
Product Data		
Order product name	Stan 25W E14 230V P45 CL 1CT/10X10F	
Full product name	Stan 25W E14 230V P45 CL 1CT/10X10F	
Full product code	871150001183150	
Order code	921411044211	
Material Nr. (12NC)	921411044211	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	8711500011831	
Numerator - Packs per outer box	100	
EAN/UPC - Case	8711500081254	

Datasheet, 2023, September 4 data subject to change

Standard Lustre P45 clear

Dimensional drawing



Product	D	C (max)
Stan 25W E14 230V P45 CL 1CT/10X10F	45 mm	78 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.