



PAR38

PAR38 120W E27 24V SP 10D 1CT/12

Pressed-glass 121 mm diameter reflector lamps of high luminous intensity


Product data

General Information	
Cap base	E27 [E27]
Operating position	UNIVERSAL [Any or Universal (U)]
Nominal lifetime	2,000 h
Switching Cycle	8,000
Rated Lifetime (Hours)	2,000 h
Lighting Technology	Incandescent
Light Technical	
Beam angle (nom.)	10 degree(s)
Correlated Colour Temperature	2700 K
Colour rendering index (CRI)	100
Luminous flux in 90° cone (rated)	1,545 lm
Operating and Electrical	
Power Consumption	120.0 W
Starting time (nom.)	0.0 s
Warm-up time to 60% light	Instant full light s
Power Factor (Fraction)	1
Voltage (nom.)	24 V
Voltage (nom.)	24 V

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb shape	PAR38 [PAR 4.75 inch/121 mm]
Approval and Application	
Energy consumption kWh/1,000 hours	127 kWh
Product Data	
Order product name	PAR38 120W E27 24V SP 10D 1CT/12
Full product name	PAR38 120W E27 24V SP 10D 1CT/12
Full EOC	871150038073915
Order code	38073915
Material no. (12 NC)	923810020511
Local order code	24120ESPAR38
SAP numerator – quantity per pack	1
EAN/UPC – Product/Case	8711500380739
Numerator – packs per outer box	12
EAN/UPC – Case	8711500381118


PAR38

Dimensional drawing



Product	D (max)	C (max)	C1
PAR38 120W E27 24V SP 10D 1CT/12	123 mm	137 mm	123 mm

Photometric data



Light Distribution Diagram - PAR38 120W E27 24V SP 10D 1CT/12

