PHILIPS

Lighting



PAR38

PAR38 80W E27 230V PAR38 FL 30D 1CT/12

Pressed-glass 121 mm diameter reflector lamps of high luminous intensity

Product data

General Information	
Cap-Base	E27 [E27]
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal lifetime	2,000 hour(s)
Switching Cycle	8,000
Rated Lifetime (Hours)	2,000 hour(s)
Lighting Technology	Incandescent

Light Technical	
Beam Angle (Nom)	30 degree(s)
Correlated Color Temperature (Nom)	2700 K
Color rendering index (CRI)	100
Luminous Flux in 90° Cone (Rated)	670 lm

Operating and Electrical	
Power Consumption	80.0 W
Starting Time (Nom)	0.0 s
Warm-up time to 60% light	instant full light s
Power Factor (Fraction)	1
Voltage (Nom)	230 V
Voltage (Nom)	230 V

Controls and Dimming	
Dimmable	Yes


Mechanical and Housing	
Bulb Shape	PAR38 [PAR 4.75 inch/121mm]

Approval and Application	
Energy Consumption kWh/1000 h	80 kWh

Product Data	
Order product name	PAR38 80W E27 230V PAR38 FL 30D 1CT/12
Full product name	PAR38 80W E27 230V PAR38 FL 30D 1CT/12
Full product code	871150090003601
Order code	923810544296
Material Nr. (12NC)	923810544296
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500900036
Numerator - Packs per outer box	12
EAN/UPC - Case	8718291115762


PAR38

Dimensional drawing



Product	D (max)	C (max)
PAR38 80W E27 230V PAR38 FL 30D 1CT/12	123 mm	137 mm

Photometric data



Light Distribution Diagram - PAR38 80W E27 230V PAR38 FL 30D 1CT/12

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.