PHILIPS Lighting



Halogen High Voltage SE (Theater)

6820P 500W GY9.5 230V 1CT/10

Two distinctive features make this lamp ideal for use in theater luminaires where long life is essential. Firstly, the filament is especially designed for extended lifetime. Secondly the highly innovative P3 technology, developed by Philips, allows the pinch to better withstand extreme heat conditions which extends the average lamp lifetime, ensures consistent high-quality light output over time, and results in fewer early failures and fewer maintenance man hour costs.


Product data

General Information				
Cap-Base	GY9.5 [GY9.5]			
Operating Position	UNIVERSAL [Any or Universal (U)]			
Life to 50% Failures (Nom)	360 hour(s)			
Light Technical				
Correlated Color Temperature (Nom)	3000 K			
Operating and Electrical				
Power Consumption	500 W			
Voltage (Nom)	230 V			
Voltage (Nom)	230 V			
<u></u>				
Controls and Dimming				
Dimmable	Yes			

Mechanical and Housing	
Bulb Finish	Clear
Product Data	
Order product name	6820P 500W GY9.5 230V 1CT/10
Full product name	6820P 500W GY9.5 230V 1CT/10
Full product code	871150018460325
Order code	923894043228
Material Nr. (12NC)	923894043228
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500184603
Numerator - Packs per outer box	10
EAN/UPC - Case	8711500184610

Halogen High Voltage SE (Theater)

Dimensional drawing



Product	D (max)	н	w	L	C (max)
6820P 500W GY9.5 230V 1CT/10	22 mm	11 mm	11 mm	46.5 mm	90 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, May 1 - data subject to change