



# Aluline 37/56

Alu 20W 12V R37 32D FR 1CT/10X5F

Low-voltage halogen burner in specialized aluminum reflector prevents heat in the backlight; bayonet cap for secure fitting

## Product data


| General Information                |                                  |
|------------------------------------|----------------------------------|
| Cap-Base                           | BA15D [BA15d]                    |
| Operating Position                 | UNIVERSAL [Any or Universal (U)] |
| Nominal lifetime                   | 2,000 hour(s)                    |
| Switching Cycle                    | 8,000                            |
| Rated Lifetime (Hours)             | 2,000 hour(s)                    |
| Lighting Technology                | Halogen                          |
| Light Technical                    |                                  |
| Beam Angle (Nom)                   | 32 degree(s)                     |
| Correlated Color Temperature (Nom) | 3000 K                           |
| Color rendering index (CRI)        | 100                              |
| Luminous Flux in 90° Cone (Rated)  | 185 lm                           |
| Operating and Electrical           |                                  |
| Power Consumption                  | 20.0 W                           |
| Lamp Current (Nom)                 | 1.67 A                           |
| Starting Time (Nom)                | 0.0 s                            |
| Warm-up time to 60% light          | instant full light s             |
| Power Factor (Fraction)            | 1                                |
| Voltage (Nom)                      | 12 V                             |
| Voltage (Nom)                      | 12 V                             |

| Controls and Dimming            |                                  |
|---------------------------------|----------------------------------|
| Dimmable                        | Yes                              |
| Mechanical and Housing          |                                  |
| Bulb Finish                     | Frosted                          |
| Bulb Shape                      | R37 [R 37mm]                     |
| Approval and Application        |                                  |
| Energy Consumption kWh/1000 h   | 21 kWh                           |
| Product Data                    |                                  |
| Order product name              | Alu 20W 12V R37 32D FR 1CT/10X5F |
| Full product name               | Alu 20W 12V R37 32D FR 1CT/10X5F |
| Full product code               | 871150040935560                  |
| Order code                      | 924001517102                     |
| Material Nr. (12NC)             | 924001517102                     |
| Numerator - Quantity Per Pack   | 1                                |
| EAN/UPC - Product/Case          | 8711500409355                    |
| Numerator - Packs per outer box | 50                               |
| EAN/UPC - Case                  | 8711500421975                    |

Dimensional drawing

| Product                          | D (max) | C (max) |
|----------------------------------|---------|---------|
| Alu 20W 12V R37 32D FR 1CT/10X5F | 38 mm   | 41 mm   |

Photometric data



Light Distribution Diagram - Alu 20W 12V R37 32D FR 1CT/10X5F

