PHILIPS Lighting



Capsuleline

CAPS 10W G4 12V CL 4000H 1CT/10X10F

Single-ended low-voltage halogen capsule giving crisp white halogen light


Product data

General Information			
Cap-Base	G4 [G4]		
Operating Position	UNIVERSAL [Any or Universal (U)]		
Nominal lifetime	4,000 hour(s)		
Switching Cycle	16,000		
Rated Lifetime (Hours)	4,000 hour(s)		
Lighting Technology	Halogen		
Light Technical			
Luminous Flux	140 lm		
Luminous Efficacy (rated) (Nom)	14 lm/W		
Color rendering index (CRI)	100		
Operating and Electrical			
Power Consumption	10.0 W		
Lamp Current (Nom)	0.83 A		
Starting Time (Nom)	0.0 s		
Warm-up time to 60% light	instant full light s		
Power Factor (Fraction)	1		
Voltage (Nom)	12 V		
Voltage (Nom)	12 V		

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	T9 [T 9mm (T9)]
Approval and Application	
Energy Consumption kWh/1000 h	11 kWh
Product Data	
Order product name	Caps 10W G4 12V CL 4000h 1CT/10X10F
Full product name	CAPS 10W G4 12V CL 4000H 1CT/10X10F
Full product code	871150040970650
Order code	40970650
Material Nr. (12NC)	924036317101
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500409706
Numerator - Packs per outer box	100
EAN/UPC - Case	8711500425645

Capsuleline

Dimensional drawing



Product	D (max)	L	C (max)
Caps 10W G4 12V CL 4000h 1CT/10X10F	9 mm	22 mm	33 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 30 - data subject to change