

Capsuleline

Caps 50W GY6.35 12V CL 4000h 1CT/10X10F

Single-ended low-voltage halogen capsule giving crisp white halogen light

Product data

General Information	
Cap-Base	GY6.35 [GY6.35]
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal lifetime	4,000 hour(s)
Switching Cycle	16,000
Rated Lifetime (Hours)	4,000 hour(s)
Lighting Technology	Halogen

Light Technical	
Luminous Flux	880 lm
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	17.2 lm/W
Color rendering index (CRI)	100

Operating and Electrical	
Power Consumption	50.0 W
Lamp Current (Nom)	4.25 A
Starting Time (Nom)	0.0 s
Warm-up time to 60% light	instant full light s
Power Factor (Fraction)	1
Voltage (Nom)	12 V
Voltage (Nom)	12 V

Controls and Dimming	
Dimmable	Yes


Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	T11 [T 11mm]

Approval and Application	
Energy Consumption kWh/1000 h	53 kWh

Product Data	
Order product name	Caps 50W GY6.35 12V CL 4000h 1CT/10X10F
Full product name	Caps 50W GY6.35 12V CL 4000h 1CT/10X10F
Full product code	871150040217250
Order code	924040217101
Material Nr. (12NC)	924040217101
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500402172
Numerator - Packs per outer box	100
EAN/UPC - Case	8711500425737

Capsuleline

Dimensional drawing



Product	D (max)	L	C (max)
Caps 50W GY6.35 12V CL 4000h 1CT/10X10F	12 mm	30 mm	44 mm

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.