



Capsuleline

CAPS 35W GY6.35 12V CL 4000H 1CT/10X10F

Single-ended low-voltage halogen capsule giving crisp white halogen light

Product data


General Information			
Cap-Base	GY6.35 [GY6.35]		
Operating Position	UNIVERSAL [Any or Universal (U)]		
Nominal lifetime	4,000 hour(s)		
Switching Cycle	16,000		
Rated Lifetime (Hours)	4,000 hour(s)		
Lighting Technology	Halogen		
Light Technical			
Luminous Flux	600 lm		
Correlated Color Temperature (Nom)	3000 K		
Luminous Efficacy (rated) (Nom)	17 lm/W		
Color rendering index (CRI)	100		
Operating and Electrical			
Power Consumption	35.0 W		
Lamp Current (Nom)	2.95 A		
Starting Time (Nom)	0.0 s		
Warm-up time to 60% light	instant full light s		
Power Factor (Fraction)	1		
Voltage (Nom)	12 V		
Voltage (Nom)	12 V		

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	T11 [T 11mm]
Approval and Application	
Energy Consumption kWh/1000 h	37 kWh
Product Data	
Order product name	Caps 35W GY6.35 12V CL 4000h 1CT/10X10F
Full product name	CAPS 35W GY6.35 12V CL 4000H 1CT/10X10F
Full product code	871150040218950
Order code	40218950
Material Nr. (12NC)	924040317101
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500402189
Numerator - Packs per outer box	100
EAN/UPC - Case	8711500425775

Datasheet, 2023, April 30 data subject to change

Capsuleline

Dimensional drawing



Product	D (max)	L	C (max)
Caps 35W GY6.35 12V CL 4000h 1CT/10X10F	12 mm	30 mm	44 mm

