



# **Essential LV MR16**

## Hal-Dich 2y 35W GU5.3 12V 36D 1CT/10X5F

The Essential LV MR16 is part of the Philips "Value for Money" ranges. It is a good choice for professional end-users looking for high-quality accent light to create contrast in shops, hotels and restaurants.

#### **Product data**


General Information	
Cap-Base	GU5.3 [GU5.3]
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal lifetime	2,000 hour(s)
Switching Cycle	8,000
Rated Lifetime (Hours)	2,000 hour(s)
Lighting Technology	Halogen
Light Technical	
Beam Angle (Nom)	36 degree(s)
Correlated Color Temperature (Nom)	3000 K
Color rendering index (CRI)	100
Luminous Flux in 90° Cone (Rated)	430 lm
Operating and Electrical	
Power Consumption	35 W
Lamp Current (Nom)	2.92 A
Starting Time (Nom)	0.0 s
Warm-up time to 60% light	instant full light s
Voltage (Nom)	12 V

Voltage (Nom)	12 V
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Shape	MR16 [2inch/50mm]
Product Data	
Order product name	Hal-Dich 2y 35W GU5.3 12V 36D 1CT/10X5F
Full product name	Hal-Dich 2y 35W GU5.3 12V 36D 1CT/10X5F
Full product code	872790025243960
Order code	924049617114
Material Nr. (12NC)	924049617114
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8727900252439
Numerator - Packs per outer box	50
EAN/UPC - Case	8727900661088

Datasheet, 2023, September 4 data subject to change

### **Essential LV MR16**

#### Dimensional drawing



Product	D (max)	C (max)
Hal-Dich 2y 35W GU5.3 12V 36D 1CT/10X5F	51 mm	46 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.