



# Accentline

## Accent 35W GU5.3 12V 36D 1CT/10X5F

Low-voltage halogen burner in glass reflector. Ideal solution for small decorative luminaires, putting your objects in the spotlight. Dichroic coating prevents heat transmission onto the object.

#### Product data

General Information	
Cap-Base	GU5.3 [GU5.3]
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal lifetime	2,000 hour(s)
Switching Cycle	8,000
Rated Lifetime (Hours)	2,000 hour(s)
Lighting Technology	Halogen
Light Technical	
Beam Angle (Nom)	36 degree(s)
Correlated Color Temperature (Nom)	3000 K
Color rendering index (CRI)	100
Luminous Flux in 90° Cone (Rated)	430 lm
Operating and Electrical	
Power Consumption	35 W
Lamp Current (Nom)	2.92 A
Starting Time (Nom)	0.0 s
Voltage (Nom)	12 V
Voltage (Nom)	12 V

Controls and Dimming		
Dimmable	Yes	
Mechanical and Housing		
Bulb Shape	MR16 [2inch/50mm]	
Product Data		
Order product name	Accent 35W GU5.3 12V 36D 1CT/10X5F	
Full product name	Accent 35W GU5.3 12V 36D 1CT/10X5F	
Full product code	871150041202700	
Order code	924049617191	
Material Nr. (12NC)	924049617191	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	8711500412027	
Numerator - Packs per outer box	50	
EAN/UPC - Case	8718291756026	

### Accentline

#### Dimensional drawing

Product	D (max)	C (max)
Accent 35W GU5.3 12V 36D 1CT/10X5F	51 mm	46 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, September 4 - data subject to change