



Brilliantline Dichroic

Halogen LV MR16 35W GU5.3 12V 60D 2PF/10

Low-voltage, xenon gas-filled halogen burner with axial filament optically positioned in a glass reflector

Product data

General Information	
Cap-Base	GU5.3 [GU5.3]
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal lifetime	4,000 h
Switching Cycle	16,000
Rated Lifetime (Hours)	4,000 h
Lighting Technology	Halogen
Light Technical	
Beam Angle (Nom)	60 degree(s)
Correlated Color Temperature (Nom)	3000 K
Color rendering index (CRI)	100
Luminous Flux in 90° Cone (Rated)	500 lm
Operating and Electrical	
Power Consumption	35.0 W
Lamp Current (Nom)	2.9 A
Starting Time (Nom)	0.0 s
Warm-up time to 60% light	instant full light s
Power Factor (Fraction)	1
Voltage (Nom)	12 V
Voltage (Nom)	12 V

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	MR16 [2inch/50mm]
Approval and Application	
Energy Consumption kWh/1000 h	37 kWh
Product Data	
Order product name	Halogen LV MR16 35W GU5.3 12V 60D 2PF/10
Full product name	Halogen LV MR16 35W GU5.3 12V 60D 2PF/10
Full product code	871829122160900
Order code	924050717107
Material Nr. (12NC)	924050717107
Local order code	15122
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291221609
Numerator - Packs per outer box	100
EAN/UPC - Case	8718291221623


Brilliantline Dichroic

Dimensional drawing



Product	D (max)	C (max)
Halogen LV MR16 35W GU5.3 12V 60D 2PF/10	51 mm	46 mm

Photometric data



Light Distribution Diagram - Halogen LV MR16 35W GU5.3 12V 60D 2PF/10

