

MASTERLine 111

MASTERLine 111 45W G53 12V 24D 1CT/6

Low-voltage halogen reflector lamp with double-ended burner and high-purity aluminium reflector

Product data

General Information	
Cap-Base	G53 [G53]
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal lifetime	4,000 hour(s)
Switching Cycle	16,000
Rated Lifetime (Hours)	4,000 hour(s)
Lighting Technology	Halogen

Light Technical	
Beam Angle (Nom)	24 degree(s)
Correlated Color Temperature (Nom)	3000 K
Color rendering index (CRI)	100
Luminous Flux in 90° Cone (Rated)	640 lm

Operating and Electrical	
Power Consumption	45.0 W
Lamp Current (Nom)	3.8 A
Starting Time (Nom)	0.0 s
Warm-up time to 60% light	instant full light s
Power Factor (Fraction)	1
Voltage (Nom)	12 V
Voltage (Nom)	12 V

Controls and Dimming	
Dimmable	Yes


Mechanical and Housing	
Bulb Shape	R111 [R 111mm]

Approval and Application	
Energy Consumption kWh/1000 h	48 kWh

Product Data	
Order product name	MASTERLine 111 45W G53 12V 24D 1CT/6
Full product name	MASTERLine 111 45W G53 12V 24D 1CT/6
Full product code	871150041107510
Order code	924058717161
Material Nr. (12NC)	924058717161
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500411075
Numerator - Packs per outer box	6
EAN/UPC - Case	8711500437341


MASTERLine 111

Dimensional drawing



Product	D (max)	C (max)	C1 (max)
MASTERLine 111 45W G53 12V 24D 1CT/6	111 mm	67 mm	51 mm

Photometric data



Light Distribution Diagram - MASTERLine 111 45W G53 12V 24D 1CT/6

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.