



# **HPL**

### **HPL750W 115V 10PK**

HPL lamps include a barrel-shaped filament that is approved by ETC for use in its Source Four  $^{\text{TM}}$  fixtures. Bright, high quality light and high beam intensity is assured by the optimal filament design, while the unique P3 technology, developed by Philips, allows the lamp to be used at higher temperatures, which extends lifetime and consistency of high-quality light output, resulting in fewer early failures and fewer maintenance man hour costs.

#### **Product data**


General Information					
Cap-Base	HEATSINK [Heat Sink]				
Operating Position	UNIVERSAL [Any or Universal (U)]				
Life to 50% Failures (Nom)	300 hour(s)				
Light Technical					
Color rendering index (CRI)	100				
Operating and Electrical					
Power Consumption	750 W 115 V				
Voltage (Nom)	115 V				
Voltage (Nom)	115 V				
Controls and Dimming					
Dimmable	Yes				

Machanical and Housing					
Mechanical and Housing					
Bulb Finish	Clear				
Product Data					
Order product name	7008 750W Heat Sink 115V 1CT/10				
Full product name	HPL750W 115V 10PK				
Full product code	871150018537225				
Order code	391714				
Material Nr. (12NC)	924555134428				
Numerator - Quantity Per Pack	1				
EAN/UPC - Product/Case	8711500185372				
Numerator - Packs per outer box	10				
EAN/UPC - Case	8711500185488				

Datasheet, 2023, April 30 data subject to change

## **HPL**

## Dimensional drawing



Product	D (max)	Н	w	D1	L	C (max)
7008 750W Heat Sink 115V	19 mm	10.5 mm	6.3 mm	6.3 mm	60.3 mm	104 mm
1CT/10						

