

HalogenA PAR30S

HalogenA Par30s 75W E27 230V 25D 1CT/15

Mains-voltage 97 mm diameter reflector lamp

Product data

General Information	
Cap-Base	E27
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal lifetime	2,000 hour(s)
Switching Cycle	8,000
Rated Lifetime (Hours)	2,000 hour(s)
Lighting Technology	Halogen

Light Technical	
Beam Angle (Nom)	30 degree(s)
Correlated Color Temperature (Nom)	2800 K
Color rendering index (CRI)	100
Luminous Flux in 90° Cone (Rated)	725 lm

Operating and Electrical	
Power Consumption	75.0 W
Starting Time (Nom)	0.0 s
Warm-up time to 60% light	instant full light s
Power Factor (Fraction)	1
Voltage (Nom)	230 V
Voltage (Nom)	230 V

Controls and Dimming	
Dimmable	Yes


Mechanical and Housing	
Bulb Shape	PAR30S

Approval and Application	
Energy Consumption kWh/1000 h	75 kWh

Product Data	
Order product name	HalogenA Par30s 75W E27 230V 25D 1CT/15
Full product name	HalogenA Par30s 75W E27 230V 25D 1CT/15
Full product code	871150088701600
Order code	924710844281
Material Nr. (12NC)	924710844281
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500887016
Numerator - Packs per outer box	15
EAN/UPC - Case	8711500887030


HalogenA PAR30S

Dimensional drawing



Product	D (max)	C (max)
HalogenA Par30s 75W E27 230V 25D 1CT/15	96 mm	99 mm

Photometric data



Light Distribution Diagram - HalogenA Par30s 75W E27 230V 25D 1CT/15

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.