PHILIPS

Lighting



Halogen reflector

JCR 12-100 H10.1CT/24

Philips' halogen reflector lamps offer the ideal no-fuss solution for a wide variety of medical, projection and scientific illumination systems. Their proven reliability makes them ideal for retrofit installations. The burners are precisely aligned for optimal light performance. Dichroic reflectors ensure heat dissipation towards the back of the optical system, which helps the optical system remain within temperature limits. A special blue-filter version blocking out unwanted light above 700 nm is available for dental curing applications. In addition, you get all the proven advantages of halogen technology such as a CRI of 100 – the same as natural sunlight for the best possible color rendering. Halogen lamps also create a comfortable warm white light, and they maintain their high lumen output with almost no lumen reduction throughout their lifetime.

产品数据

一般信息	
底盖	GZ6.35 [GZ6.35]
操作位置	S90 [直立 +/-90D 或底座朝下 (BDH)]
50% 故障条件下的使用寿命 (标称)	1,000 小时

灯技术	
相关色温 (标称)	3100 K
显色指数 (CRI)	100

操作和电气	
功耗	100 W
电压 (标称)	12 V
电压 (标称)	12 V

控制和调光	
可调光	是


机械和外壳	
灯泡材料	开放紫外线石英
反射器外观	光滑
灯泡外形	R50 [R 50 毫米]

产品数据	
订单产品名称	JCR 12-100 H10.1CT/24
完整的产品名称	JCR 12-100 H10.1CT/24
完整产品代码	871150044129430
订购代码	924812017194
材料编号 (12NC)	924812017194
计算器 - 每包数量	1
EAN/UPC - 产品/箱	8711500441294

Halogen reflector

计算器 - 每个外包装箱中的包数	24
EAN/UPC - 案例	8711500441300

二维绘图



Product	D (max)	C (max)
JCR 12-100 H10.1CT/24	50 mm	42 mm

© 2023 Signify Holding 保留所有权利。 Signify 对此文档所包含信息的准确性或完整性不作任何陈述或保证，也不对根据此文档信息做出的任何行为负责。 本文档中提供的信息不作为任何商业要约，也不构成任何报价或合同的一部分，除非 Signify 同意。
Philips 和 Philips Shield Emblem 是 Koninklijke Philips N.V. 的注册商标。