



MASTERCapsule

MASTERCAPS 60W GY6.35 12V IR 1CT/5X10F

MASTERCapsule with EcoBoost Technology: highest halogen capsule energy savings, 40% more savings than standard capsules

Product data


General Information			
Cap-Base	GY6.35 [GY6.35]		
Operating Position	UNIVERSAL [Any or Universal (U)]		
Nominal lifetime	4,000 hour(s)		
Switching Cycle	16,000		
Rated Lifetime (Hours)	4,000 hour(s)		
Lighting Technology	Halogen		
Light Technical			
Luminous Flux	1,700 lm		
Correlated Color Temperature (Nom)	3000 K		
Luminous Efficacy (rated) (Nom)	26 lm/W		
Color rendering index (CRI)	100		
Operating and Electrical			
Power Consumption	60.0 W		
Lamp Current (Nom)	5 A		
Starting Time (Nom)	0.0 s		
Warm-up time to 60% light	instant full light s		
Power Factor (Fraction)	1		
Voltage (Nom)	12 V		
Voltage (Nom)	12 V		

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	IR Coated
Bulb Shape	T11 [T 11mm]
Approval and Application	
Energy Consumption kWh/1000 h	64 kWh
Product Data	
Order product name	MASTERCaps 60W GY6.35 12V IR 1CT/5X10F
Full product name	MASTERCAPS 60W GY6.35 12V IR 1CT/5X10F
Full product code	872790020356170
Order code	20356170
Material Nr. (12NC)	924898517102
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8727900203561
Numerator - Packs per outer box	50
EAN/UPC - Case	8727900203943

Datasheet, 2023, April 30 data subject to change

MASTERCapsule

Dimensional drawing



Product	D (max)	L	C (max)
MASTERCaps 60W GY6.35 12V IR 1CT/5X10F	12 mm	30 mm	44 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.