



Halogen Twist GU10

EcoHalo Tw 35W GU10 230V 40D 1CT/10X5F

Mains-voltage halogen in glass reflector. Ideal solution for small decorative luminaires, putting your objects in a superior-quality spot light. Aluminum coating reduces heat in the backlight.


Product data

General Information	
Cap-Base	GU10 [GU10]
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal lifetime	2,000 hour(s)
Switching Cycle	8,000
Rated Lifetime (Hours)	2,000 hour(s)
Lighting Technology	Halogen
Light Technical	
Beam Angle (Nom)	40 degree(s)
Correlated Color Temperature (Nom)	2800 K
Color rendering index (CRI)	100
Luminous Flux in 90° Cone (Rated)	270 lm
Operating and Electrical	
Power Consumption	35.0 W
Lamp Current (Nom)	0.15 A
Starting Time (Nom)	0.0 s
Warm-up time to 60% light	instant full light s
Power Factor (Fraction)	1
Voltage (Nom)	230 V
Voltage (Nom)	230 V

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	MR16 [2inch/50mm]
Approval and Application	
Energy Consumption kWh/1000 h	35 kWh
Product Data	
Order product name	EcoHalo Tw 35W GU10 230V 40D 1CT/10X5F
Full product name	EcoHalo Tw 35W GU10 230V 40D 1CT/10X5F
Full product code	872790086404500
Order code	925641044205
Material Nr. (12NC)	925641044205
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8727900864045
Numerator - Packs per outer box	50
EAN/UPC - Case	8727900864069

Halogen Twist GU10

Dimensional drawing



Product	D (max)	C (max)
EcoHalo Tw 35W GU10 230V 40D 1CT/10X5F	50.7 mm	51 mm

