PHILIPS Lighting



Halogen Classic P45

Halogen 28W E14 230V P45 1CT/15 SRP

Philips Halogen Classic light bulbs offer the classical shapes you are used to. This new 'classic' gives high-quality light, is dimmable and starts immediately.


Product data

General Information		
Cap-Base	E14 [E14]	
Operating Position	UNIVERSAL [Any or Universal (U)]	
Nominal lifetime	2,000 hour(s)	
Switching Cycle	8,000	
Rated Lifetime (Hours)	2,000 hour(s)	
Lighting Technology	Halogen	
Light Technical		
Luminous Flux	370 lm	
Correlated Color Temperature (Nom)	2800 K	
Luminous Efficacy (rated) (Nom)	12.4 lm/W	
Color rendering index (CRI)	100	
Operating and Electrical		
Power Consumption	28.0 W	
Lamp Current (Nom)	0.12 A	
Starting Time (Nom)	0.0 s	
Warm-up time to 60% light	instant full light s	
Power Factor (Fraction)	1	
Voltage (Nom)	230 V	
Voltage (Nom)	230 V	

Controls and Dimming		
Dimmable	Yes	
Mechanical and Housing		
Bulb Finish	Clear	
Bulb Shape	P45 [P 45mm]	
Approval and Application		
Energy Consumption kWh/1000 h	28 kWh	
Product Data		
Order product name	Halogen 28W E14 230V P45 1CT/15 SRP	
Full product name	Halogen 28W E14 230V P45 1CT/15 SRP	
Full product code	872790083146704	
Order code	925648044238	
Material Nr. (12NC)	925648044238	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	8727900831467	
Numerator - Packs per outer box	15	
EAN/UPC - Case	8718696462874	

Halogen Classic P45

Dimensional drawing



Product	D (max)	C (max)
Halogen 28W E14 230V P45 1CT/15 SRP	46 mm	80 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, September 4 - data subject to change