



# **Halogen Classic P45**

## ClassicHalo 30 28W B22 240V P45 CL 2PF

Philips Halogen Classic light bulbs offer the classical shapes you are used to. This new 'classic' gives high-quality light, is dimmable and starts immediately.

#### **Product data**


General Information	
Cap-Base	B22 [B22]
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal lifetime	2,000 h
Switching Cycle	8,000
Rated Lifetime (Hours)	2,000 h
Lighting Technology	Halogen
Light Technical	
Luminous Flux	370 lm
Correlated Color Temperature (Nom)	2800 K
Luminous Efficacy (rated) (Nom)	12.4 lm/W
Color rendering index (CRI)	100
Operating and Electrical	
Power Consumption	28 W
Lamp Current (Nom)	0.12 A
Starting Time (Nom)	0.0 s
Warm-up time to 60% light	instant full light s
Power Factor (Fraction)	1
Voltage (Nom)	240 V
Voltage (Nom)	240 V
Voltage (Nom)	240 V

Controls and Dimming		
Dimmable	Yes	
Mechanical and Housing		
Bulb Finish	Clear	
Bulb Shape	P45 [P 45mm]	
Product Data		
Order product name	ClassicHalo 30 28W B22 240V P45 CL 2PF	
Full product name	ClassicHalo 30 28W B22 240V P45 CL 2PF	
Full product code	871829121978100	
Order code	925648645503	
Material Nr. (12NC)	925648645503	
Local order code	LCL28W240VBC	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	8718291219781	
Numerator - Packs per outer box	100	
EAN/UPC - Case	8718291219804	

Datasheet, 2023, April 29 data subject to change

# Halogen Classic P45

### Dimensional drawing



Product	D (max)	C (max)
ClassicHalo 30 28W B22 240V P45 CL 2PF	46 mm	72.5 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.