



# Halogen Classic Ashape

## ClassicHalogen28W E27 240V A55 CL 1CT/10

Philips Halogen Classic light bulbs offer the classical shapes you are used to. This new 'classic' gives high-quality light, is dimmable and starts immediately.

#### **Product data**

General Information	
Cap-Base	E27 [E27]
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal lifetime	2,000 hour(s)
Switching Cycle	8,000
Rated Lifetime (Hours)	2,000 hour(s)
Lighting Technology	Halogen
Light Technical	
Luminous Flux	370 lm
Correlated Color Temperature (Nom)	2800 K
Luminous Efficacy (rated) (Nom)	12.4 lm/W
Color rendering index (CRI)	100
Operating and Electrical	
Power Consumption	28.0 W
Lamp Current (Nom)	0.12 A
Starting Time (Nom)	0.0 s
Warm-up time to 60% light	instant full light s
Power Factor (Fraction)	1
Voltage (Nom)	240 V
Voltage (Nom)	240 V

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	A55 [A 55mm]
Approval and Application	
Energy Consumption kWh/1000 h	28 kWh
Product Data	
Order product name	ClassicHalogen28W E27 240V A55 CL 1CT/10
Full product name	ClassicHalogen28W E27 240V A55 CL 1CT/10
Full product code	872790089472101
Order code	925692945502
Material Nr. (12NC)	925692945502
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8727900894721
Numerator - Packs per outer box	100
EAN/UPC - Case	8718291126393

Datasheet, 2023, September 4 data subject to change

## Halogen Classic A-shape

### Dimensional drawing

Product	D (max)	C (max)
ClassicHalogen28W E27 240V A55 CL 1CT/10	56 mm	97 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.