

# **Halogen Deco**

## BC25BA11/E26/EV/CL120V 6/2 TP

Halogen bulbs reduce energy consumption without sacrificing the qualities of a traditional bulb. They uniquely produce light more efficiently. They work with dimmer switches and are available in the familiar G25 & G16.5 globes, bent and blunt tip candles, and flames. Use them in existing fixtures just as you would standard incandescents and your home will look great while you save energy.

#### **Product data**


General Information		
Cap-Base	E26 [Single Contact Medium Screw]	
Operating Position	UNIVERSAL [Any or Universal (U)]	
Nominal lifetime	2,500 hour(s)	
Rated Lifetime (Hours)	2,500 hour(s)	
Lighting Technology	Halogen	
Light Technical		
Luminous Flux	280 lm	
Correlated Color Temperature (Nom)	2700 K	
Color rendering index (CRI)	100	
Operating and Electrical		
Power Consumption	25 W	
Lamp Current (Nom)	0.21 A	
Starting Time (Nom)	0.0 s	
Voltage (Nom)	120 V	
Voltage (Nom)	120 V	

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	BA11 [BA11 35mm]
Product Data	
Order product name	BC25BA11/E26/EV/CL120V 6/2 TP
Full product name	BC25BA11/E26/EV/CL120V 6/2 TP
Order code	925708636301
Material Nr. (12NC)	925708636301
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677424251
Numerator - Packs per outer box	6
EAN/UPC - Case	50046677424256

Datasheet, 2023, September 4 data subject to change

### **Halogen Deco**

#### Dimensional drawing



Product	D (max)	C (max)
BC25BA11/E26/EV/CL120V 6/2 TP	36 mm	100 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.