



U-Bent Rapid Start T8

FB29T8/TL835/EW/ALTO 15/1

Philips leads the industry with the lowest level mercury technology. Reducing the mercury level (source reduction) during the manufacturing phase is essential to creating products that are less harmful to the environment.

Warnings and Safety

- · Lamp contains mercury.
- · Manage in Accord with Disposal Laws.
- See: www.lamprecycle.org or 1-800-555-0050

Product data

General Information	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Features	ALTO® (ALTO)
Light Technical	
Color Code	TL835 [CCT of 3500K (835)]
Luminous Flux	2,550 lm
Correlated Color Temperature (Nom)	4100 K
Color rendering index (CRI)	85
Operating and Electrical	
Power Consumption	29 W
Mechanical and Housing	
Bulb Shape	T8-1-5/8U [U-bent T linch with 1-5/8" leg spacing]

Approval and Application	
Energy Saving Product	Energy Saving
Mercury (Hg) Content (Nom)	3.0 mg
Product Data	
Order product name	FB29T8/TL835/EW/ALTO 15/1
Full product name	FB29T8/TL835/EW/ALTO 15/1
Order code	226761
Material Nr. (12NC)	927861383502
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677226763
Numerator - Packs per outer box	15
EAN/UPC - Case	50046677226768

Datasheet, 2023, April 30 data subject to change

U-Bent Rapid Start T8

Dimensional drawing

Product

FB29T8/TL835/EW/ALTO 15/1





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.