



# **MASTER PL-C 2 Pin**

# MASTER PL-C 13W/840/2P 1CT/5X10BOX

Energy-saving compact fluorescent lamps. Compact long-arc low-pressure mercury discharge lamp. Envelope consists of 4 parallel narrow fluorescent tubes

### **Warnings and Safety**

- $\cdot$  Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- · Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

#### **Product data**

General Information					
Cap-Base	G24d-1				
Life to 50% Failures (Nom)	10,000 h				
Light Technical					
Color Code	840 [CCT of 4000K]				
Luminous Flux	925 lm				
Color Designation	Cool White (CW)				
Correlated Color Temperature (Nom)	4000 K				
Luminous Efficacy (rated) (Nom)	69 lm/W				
Color rendering index (CRI)	82				
Operating and Electrical					
Power Consumption	13.4 W				
Lamp Current (Nom)	0.170 A				


Controls and Dimming					
Dimmable	No				
Approval and Application					
Mercury (Hg) Content (Nom)	1.4 mg				
Energy Consumption kWh/1000 h	17 kWh				
	·				
Product Data					
Order product name	MASTER PL-C 13W/840/2P 1CT/5X10BOX				
Full product name	MASTER PL-C 13W/840/2P 1CT/5X10BOX				
Full product code	871150062086600				
Local code description	PLC13W8402P				
Order code	927904884002				
Material Nr. (12NC)	927904884002				
Local order code	PLC13W8402P				
Numerator - Quantity Per Pack	1				

Datasheet, 2023, April 17 data subject to change

# **MASTER PL-C 2 Pin**


EAN/UPC - Product/Case	8711500620866		
Numerator - Packs per outer box	50		
EAN/UPC - Case	8711500621122		

## Dimensional drawing




Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-C 13W/840/2P 1CT/	27.1 mm	27.1 mm	97.5 mm	117.0 mm	139.4 mm
5X10BOX					


#### Photometric data



Spectral Power Distribution Colour - MASTER PL-C 13W/840/2P 1CT/5X10BOX

#### Lifetime





Life Expectancy Diagram - MASTER PL-C 13W/840/2P 1CT/5X10BOX

Lumen Maintenance Diagram - MASTER PL-C 13W/840/2P 1CT/5X10BOX

# **MASTER PL-C 2 Pin**

Lifetime

Life Expectancy Diagram - MASTER PL-C 13W/840/2P 1CT/5X10BOX



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.