



MASTER PL-C 2 Pin

MASTER PL-C 18W/865/2P 1CT/5X10BOX

Energy-saving compact fluorescent lamps. Compact long-arc low-pressure mercury discharge lamp. Envelope consists of 4 parallel narrow fluorescent tubes

Warnings and Safety

- \cdot Use only with electromagnetic control gear
- \cdot Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		Color rendering index (CRI)	82
Cap-Base	G24d-2		
Life to 50% Failures (Nom)	10,000 hour(s)	Operating and Electrical	
		Power Consumption	17.9 W
Light Technical		Lamp Current (Nom)	0.230 A
Color Code	865 [CCT of 6500K]		
Luminous Flux	1,200 lm	Controls and Dimming	
Color Designation	Cool Daylight	Dimmable	No
Correlated Color Temperature (Nom)	6500 K		
Luminous Efficacy (rated) (Nom)	67 lm/W		


MASTER PL-C 2 Pin

Approval and Application					
Mercury (Hg) Content (Nom)	1.4 mg				
Energy Consumption kWh/1000 h	22 kWh				
Product Data					

Order product name	MASTER PL-C 18W/865/2P 1CT/5X10BOX		
Full product name	MASTER PL-C 18W/865/2P 1CT/5X10BOX		
Full product code	871150063527300		


Order code	927905786502		
Material Nr. (12NC)	927905786502		
Numerator - Quantity Per Pack	1		
EAN/UPC - Product/Case	8711500635273		
Numerator - Packs per outer box	50		
EAN/UPC - Case	8711500635297		

Dimensional drawing



Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-C 18W/865/2P 1CT/	27.1 mm	27.1 mm	109.5 mm	128.0 mm	150.4 mm
5X10BOX					


Photometric data



Spectral Power Distribution Colour - MASTER PL-C 18W/865/2P 1CT/5X10BOX

MASTER PL-C 2 Pin

Lifetime



Life Expectancy Diagram - MASTER PL-C 18W/865/2P 1CT/5X10BOX

Lumen Maintenance Diagram - MASTER PL-C 18W/865/2P 1CT/5X10BOX

Life Expectancy Diagram - MASTER PL-C 18W/865/2P 1CT/5X10BOX



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 17 - data subject to change