



# **MASTER PL-C 2 Pin**

## MASTER PL-C 26W/827/2P 1CT/5X10BOX

Energy-saving compact fluorescent lamps. Compact long-arc low-pressure mercury discharge lamp. Envelope consists of 4 parallel narrow fluorescent tubes

#### Warnings and Safety

- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

#### **Product data**

General Information		Operating and Electrical		
Cap-Base	G24d-3	Power Consumption	26.5 W	
Flux measurement reference	Sphere	Lamp Current (Nom)	0.335 A	
Life to 50% Failures (Nom)	10,000 hour(s)			
		Controls and Dimming		
Light Technical		Dimmable	No	
Color Code	827 [CCT of 2700K]			
Luminous Flux	1,800 lm	Approval and Application		
Color Designation	Incandescent White	Energy Efficiency Class	G	
Chromaticity Coordinate X (Nom)	0.463	Mercury (Hg) Content (Max)	1.4 mg	
Chromaticity Coordinate Y (Nom)	0.42	Mercury (Hg) Content (Nom)	1.4 mg	
Correlated Color Temperature (Nom)	2700 K	Energy Consumption kWh/1000 h	27 kWh	
Luminous Efficacy (rated) (Nom)	68 lm/W	EPREL Registration Number	423286	
Color rendering index (CRI)	81			
		Product Data		
		Order product name	MASTER PL-C 26W/827/2P 1CT/5X10BOX	


G <sup>A</sup>

## MASTER PL-C 2 Pin

Full product name	MASTER PL-C 26W/827/2P 1CT/5X10BOX			
Full product code	871150062095870			
Order code	62095870			
Material Nr. (12NC)	927906182740			
Numerator - Quantity Per Pack	1			


EAN/UPC - Product/Case	8711500620958			
Numerator - Packs per outer box	50			
EAN/UPC - Case	8711500715913			

## Dimensional drawing




Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-C 26W/827/2P 1CT/	27.1 mm	27.1 mm	130.5 mm	149.0 mm	171.4 mm
5X10BOX					

### Photometric data




Spectral Power Distribution Colour - MASTER PL-C 26W/827/2P 1CT/5X10BOX

Lifetime



Life Expectancy Diagram - MASTER PL-C 26W/827/2P 1CT/5X10BOX



Lumen Maintenance Diagram - MASTER PL-C 26W/827/2P 1CT/5X10BOX

## MASTER PL-C 2 Pin

Lifetime

Life Expectancy Diagram - MASTER PL-C 26W/827/2P 1CT/5X10BOX



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 15 - data subject to change