



MASTER PL-C 2 Pin

MASTER PL-C 26W/865/2P 1CT/5X10BOX

Energy-saving compact fluorescent lamps. Compact long-arc low-pressure mercury discharge lamp. Envelope consists of 4 parallel narrow fluorescent tubes

Warnings and Safety

- $\boldsymbol{\cdot}$ Use only with electromagnetic control gear
- · Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- · Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

| General Information | | | |
|------------------------------------|--------------------|--|--|
| Cap-Base | G24D-3 [G24d-3] | | |
| Life to 50% Failures (Nom) | 10,000 hour(s) | | |
| | | | |
| Light Technical | | | |
| Color Code | 865 [CCT of 6500K] | | |
| Luminous Flux | 1,740 lm | | |
| Color Designation | Cool Daylight | | |
| Correlated Color Temperature (Nom) | 6500 K | | |
| Luminous Efficacy (rated) (Nom) | 66 lm/W | | |

| Color rendering index (CRI) | 80 |
|-----------------------------|---------|
| | |
| Operating and Electrical | |
| Power Consumption | 26.5 W |
| Lamp Current (Nom) | 0.335 A |
| | |
| Controls and Dimming | |
| Dimmable | No |
| | |


Datasheet, 2023, April 30 data subject to change

MASTER PL-C 2 Pin

| Approval and Application | | | | |
|-------------------------------|------------------------------------|--|--|--|
| Mercury (Hg) Content (Nom) | 1.4 mg | | | |
| Energy Consumption kWh/1000 h | 32 kWh | | | |
| | | | | |
| Product Data | | | | |
| Order product name | MASTER PL-C 26W/865/2P 1CT/5X10BOX | | | |
| Full product name | MASTER PL-C 26W/865/2P 1CT/5X10BOX | | | |
| Full product code | 871150063531000 | | | |


| Order code | 927906186502 |
|---------------------------------|---------------|
| Material Nr. (12NC) | 927906186502 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 8711500635310 |
| Numerator - Packs per outer box | 50 |
| EAN/UPC - Case | 8711500635334 |
| | |

Dimensional drawing



| Product | D (max) | D1 (max) | A (max) | B (max) | C (max) |
|-----------------------------|---------|----------|----------|----------|----------|
| MASTER PL-C 26W/865/2P 1CT/ | 27.1 mm | 27.1 mm | 130.5 mm | 149.0 mm | 171.4 mm |
| 5X10BOX | | | | | |


Photometric data




Spectral Power Distribution Colour - MASTER PL-C 26W/865/2P 1CT/5X10BOX

MASTER PL-C 2 Pin


Lifetime





Life Expectancy Diagram - MASTER PL-C 26W/865/2P 1CT/5X10BOX

Life Expectancy Diagram - MASTER PL-C 26W/865/2P 1CT/5X10BOX



Lumen Maintenance Diagram - MASTER PL-C 26W/865/2P 1CT/5X10BOX



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.