



MASTER PL-C Xtra 2 Pin



MASTER PL-C Xtra 26W/840/2P 1CT/5X10BOX

This is an efficient compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications. MASTER PL-C Xtra lamps furthermore provide significantly lower operating costs thanks to their lifetime, which is more than double that of a standard MASTER PL-C lamp, and their very low early failure rate. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base.

Warnings and Safety

- \cdot Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- · Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information				
Cap-Base	G24D-3 [G24d-3]			
Flux measurement reference	Sphere			
Life to 50% Failures (Nom)	16,000 hour(s)			
Light Technical				
Color Code	840 [CCT of 4000K]			
Luminous Flux	1,800 lm			
	<u> </u>			

Color Designation	Cool White (CW)		
Chromaticity Coordinate X (Nom)	0.38		
Chromaticity Coordinate Y (Nom)	0.38		
Correlated Color Temperature (Nom)	4000 K		
Luminous Efficacy (rated) (Nom)	68 lm/W		
Color rendering index (CRI)	80		


Datasheet, 2023, November 2 data subject to change

MASTER PL-C Xtra 2 Pin

Operating and Electrical	
Power Consumption	26.7 W
Lamp Current (Nom)	0.325 A
Controls and Dimming	
Dimmable	No
Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) Content (Max)	3 mg
Mercury (Hg) Content (Nom)	3.0 mg
Energy Consumption kWh/1000 h	27 kWh
EPREL Registration Number	423290


Product Data				
Order product name	MASTER PL-C Xtra 26W/840/2P 1CT/5X10BO			
Full product name	MASTER PL-C Xtra 26W/840/2P 1CT/5X10BOX			
Full product code	871150089886970			
Order code	927906284014			
Material Nr. (12NC)	927906284014			
Numerator - Quantity Per Pack	1			
EAN/UPC - Product/Case	8711500898869			
Numerator - Packs per outer box	50			
EAN/UPC - Case	8711500898883			

Dimensional drawing



Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-C Xtra 26W/840/2P	27.1 mm	27.1 mm	130.7 mm	149.0 mm	171.4 mm
1CT/5X10BOX					


Photometric data




Spectral Power Distribution Colour - MASTER PL-C Xtra 26W/840/2P 1CT/5X10BOX


MASTER PL-C Xtra 2 Pin


Lifetime






Life Expectancy Diagram - MASTER PL-C Xtra 26W/840/2P 1CT/5X10BOX







Life Expectancy Diagram - MASTER PL-C Xtra 26W/840/2P 1CT/5X10BOX

Lumen Maintenance Diagram - MASTER PL-C Xtra 26W/840/2P 1CT/ 5X10BOX



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.