



# MASTER PL-C Xtra 4 Pin



# MASTER PL-C Xtra 18W/830/4P 1CT/5X10BOX

MASTER PL-C Xtra is an efficient compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications. MASTER PL-C Xtra lamps furthermore provide significantly lower operating costs thanks to their lifetime, which is more than double that of a standard MASTER PL-C lamp, and their very low early failure rate. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 4-pin version is designed for operation on electronic HF control gear with integrated pre-heat and is provided with a plug-in/pull-out lamp base.

### **Warnings and Safety**

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- $\cdot$  Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### **Product data**

General Information			
Cap-Base	G24q-2		
Flux measurement reference	Sphere		
Light Technical			
Color Code	830 [CCT of 3000K]		
Luminous Flux	1,200 lm		
Color Designation	Warm White (WW)		

Chromaticity Coordinate X (Nom)	0.44
Chromaticity Coordinate Y (Nom)	0.403
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	73 lm/W
Color rendering index (CRI)	82
Operating and Electrical	
Power Consumption	18.4 W


Datasheet, 2024, March 21 data subject to change

# **MASTER PL-C Xtra 4 Pin**

Lamp Current (Nom)	0.210 A
Controls and Dimming	
Dimmable	Yes
Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) Content (Max)	3 mg
Mercury (Hg) Content (Nom)	3.0 mg
Energy Consumption kWh/1000 h	19 kWh
EPREL Registration Number	423294


Product Data					
Order product name	MASTER PL-C Xtra 18W/830/4P 1CT/5X10BOX				
Full product name	MASTER PL-C Xtra 18W/830/4P 1CT/5X10BOX				
Full product code	871150095033870				
Order code	927906583014				
Material Nr. (12NC)	927906583014				
Numerator - Quantity Per Pack	1				
EAN/UPC - Product/Case	8711500950338				
Numerator - Packs per outer box	50				
EAN/UPC - Case	8711500950352				

# Dimensional drawing



Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-C Xtra 18W/830/4P	27.1 mm	27.1 mm	109.7 mm	128.0 mm	142.9 mm
1CT/5X10BOX					


## Photometric data




Spectral Power Distribution Colour - MASTER PL-C Xtra 18W/830/4P 1CT/5X10BOX


# **MASTER PL-C Xtra 4 Pin**


### Lifetime






Life Expectancy Diagram - MASTER PL-C Xtra 18W/830/4P 1CT/5X10BOX







Life Expectancy Diagram - MASTER PL-C Xtra 18W/830/4P 1CT/5X10BOX

Lumen Maintenance Diagram - MASTER PL-C Xtra 18W/830/4P 1CT/ 5X10BOX



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.