

MASTER PL-L 豪华型 4 针

MASTER PL-L 90 De Luxe 55W/930/4P 1CT/10

紧凑型节能荧光灯含 2 个并行荧光管

安全提示

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied control gear
- Shorter lamp life when often switching and not well pre-heated electrodes

产品数据

一般信息	
底盖	2G11 [2G11]

灯技术	
颜色代码	930 [CCT of 3000K]
光通量	3,650 lm
颜色名称	暖白色 (WW)
色度坐标 X (标称)	440
色度坐标 Y (标称)	403
相关色温 (标称)	3000 K
光效 (额定)(标称)	84 lm/W
显色指数 (CRI)	90

操作和电气	
功耗	55.0 W
灯具电流 (标称)	0.525 A


控制和调光	
可调光	是

审批和申请	
汞 (Hg) 含量 (标称)	4.4 mg
能耗 kWh/1000 h	61 kWh

产品数据	
订单产品名称	MASTER PL-L 90 De Luxe 55W/930/4P 1CT/10
完整的产品名称	MASTER PL-L 90 De Luxe 55W/930/4P 1CT/10
完整产品代码	871150086698125
订购代码	927908793074
材料编号 (12NC)	927908793074
计算器 - 每包数量	1
EAN/UPC - 产品/箱	8711500866981
计算器 - 每个外包装箱中的包数	10
EAN/UPC - 案例	8711500890559


MASTER PL-L 豪华型 4 针

二维绘图



Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-L 90 De Luxe 55W/930/4P 1CT/10	39.0 mm	18.0 mm	509.2 mm	535 mm	541.6 mm

光度数据



Spectral Power Distribution Colour - MASTER PL-L 90 De Luxe 55W/930/4P 1CT/10

© 2023 Signify Holding 保留所有权利。 Signify 对此文档所包含信息的准确性或完整性不作任何陈述或保证，也不对根据此文档信息做出的任何行为负责。 本文档中提供的信息不作为任何商业要约，也不构成任何报价或合同的一部分，除非 Signify 同意。
Philips 和 Philips Shield Emblem 是 Koninklijke Philips N.V. 的注册商标。