



MASTER PL-T TOP 4 Pin



MASTER PL-T TOP 18W/830/4P 1CT/5X10CC

Energy saving compact fluorescent lamp. Compact long-arc low-pressure mercury discharge lamp. Envelope consists of 6 parallel narrow fluorescent tubes. Amalgam controlled operation

Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap base	GX24Q-2 [GX24q-2]
Flux measurement reference	Sphere
Light Technical	
Colour Code	830 [CCT of 3000K]
Luminous Flux	1,160 lm
Colour designation	Warm White (WW)
Chromaticity Coordinate X (Nom)	0.44
Chromaticity Coordinate Y (Nom)	0.403
Correlated Colour Temperature	3000 K
Luminous efficacy (rated) (min.)	67 lm/W
Colour rendering index (CRI)	80


Operating and Electrical	
Power Consumption	18.7 W
Lamp current (nom.)	0.220 A
Controls and Dimming	
Dimmable	Yes
Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) content (max.)	1.4 mg
Mercury (Hg) content (nom.)	1.4 mg
Energy consumption kWh/1,000 hours	19 kWh
EPREL registration number	423324

MASTER PL-T TOP 4 Pin

Product Data	
Order product name	MASTER PL-T TOP 18W/830/4P 1CT/5X10BOX
Full product name	MASTER PL-T TOP 18W/830/4P 1CT/5X10CC
Full EOC	871150088908970
Order code	88908970
Material no. (12 NC)	927910883069
Local order code	18PLT8304PINTOP


SAP numerator – quantity per pack	1
EAN/UPC – Product/Case	8711500889089
Numerator – packs per outer box	50
EAN/UPC – Case	8711500889409

Dimensional drawing



Product	D (max)	A (max)	B (max)	C (max)
MASTER PL-T TOP 18W/830/4P 1CT/5X10BOX	41 mm	71.7 mm	96.0 mm	111.7 mm

Photometric data




Spectral Power Distribution Colour - MASTER PL-T TOP 18W/830/4P 1CT/5X10BOX

MASTER PL-T TOP 4 Pin


Lifetime



Lumen Maintenance Diagram - MASTER PL-T TOP 18W/830/4P 1CT/5X10BOX



Life Expectancy Diagram - MASTER PL-T TOP 18W/830/4P 1CT/5X10BOX



Life Expectancy Diagram - MASTER PL-T TOP 18W/830/4P 1CT/5X10BOX

