



# PL-T Triple 4-Pin Base

# PL-T 42W/830/A/4P 1CT/5X10BOX ALTO

Philips Linear Compact Fluorescent Lamps offer designers, specifiers and end-users new levels of efficiencies and versatility in sizes, configurations and application possibilities. With so many elegant fixtures available to complement their small size, high light output and advanced technology, Philips Energy Advantage lamps are fast becoming the preferred choice when maximum effciency and sleek design solutions are required.

### **Product data**


General Information			
Cap-Base	GX24q-4		
Light Technical			
Color Code	830 [CCT of 3000K]		
Luminous Flux	3,200 lm		
Color Designation	Warm White (WW)		
Correlated Color Temperature (Nom)	3000 K		
Luminous Efficacy (Rated) (Min)	80 lm/W		
Color rendering index (CRI)	>80		
Operating and Electrical			
Power Consumption	38.0 W		
Lamp Current (Nom)	0.320 A		
Controls and Dimming			
Dimmable	Yes		

Approval and Application				
Mercury (Hg) Content (Nom)	1.4 mg			
Product Data				
Order product name	PL-T 42W/830/A/4P 1CT/5X10BOX ALTO			
Full product name	PL-T 42W/830/A/4P 1CT/5X10BOX ALTO			
Order code	149013			
Material Nr. (12NC)	927911483020			
Numerator - Quantity Per Pack	1			
EAN/UPC - Product/Case	046677149017			
Numerator - Packs per outer box	10			
EAN/UPC - Case	50046677149012			

Datasheet, 2023, April 17 data subject to change


# **PL-T Triple 4-Pin Base**

### Dimensional drawing




Product	D (max)	A (max)	B (max)	C (max)
PL-T 42W/830/A/4P 1CT/5X10BOX ALTO	41 mm	120.7 mm	145.0 mm	160.7 mm


### Photometric data



Spectral Power Distribution Colour - PL-T 42W/830/A/4P 1CT/5X10BOX ALTO

## Lifetime






Lumen Maintenance Diagram - PL-T 42W/830/A/4P 1CT/5X10BOX ALTO

Life Expectancy Diagram - PL-T 42W/830/A/4P 1CT/5X10BOX ALTO

# **PL-T Triple 4-Pin Base**

### Lifetime



Life Expectancy Diagram - PL-T 42W/830/A/4P 1CT/5X10BOX ALTO

