



MASTER PL-T Xtra 4 Pin



MASTER PL-T Xtra 32W/830/4P 1CT/5X10BOX

MASTER PL-T Xtra is an efficient compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications demanding higher lighting levels. MASTER PL-T Xtra lamps furthermore provide significantly lower operating costs thanks to their lifetime, which is more than double that of a standard MASTER PL-T lamp, and their very low early failure rate. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 4-pin version is designed for operation on electronic gear and is provided with a plug-in/pull-out lamp base.

Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- \cdot Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	GX24q-3
Flux measurement reference	Sphere
Light Technical	
Color Code	830 [CCT of 3000K]
Luminous Flux	2,230 lm
Color Designation	Warm White (WW)

Chromaticity Coordinate X (Nom)	0.44
Chromaticity Coordinate Y (Nom)	0.403
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	75 lm/W
Color rendering index (CRI)	80
Operating and Electrical	
Power Consumption	32.0 W


Datasheet, 2024, March 18 data subject to change

MASTER PL-T Xtra 4 Pin

Lamp Current (Nom)	0.320 A
Controls and Dimming	
Dimmable	Yes
Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) Content (Max)	3 mg
Mercury (Hg) Content (Nom)	3.0 mg
Energy Consumption kWh/1000 h	32 kWh
EPREL Registration Number	423335
·	

Product Data	
Order product name	MASTER PL-T Xtra 32W/830/4P 1CT/5X10BOX
Full product name	MASTER PL-T Xtra 32W/830/4P 1CT/5X10BOX
Full product code	871150089740470
Order code	927912583014
Material Nr. (12NC)	927912583014
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500897404
Numerator - Packs per outer box	50
EAN/UPC - Case	8711500897428


Dimensional drawing



 Product
 D (max)
 A (max)
 B (max)
 C (max)

 MASTER PL-T Xtra 32W/830/4P 1CT/5X10BOX
 41.0 mm
 98.7 mm
 123.0 mm
 138.7 mm


Photometric data




Spectral Power Distribution Colour - MASTER PL-T Xtra 32W/830/4P 1CT/5X10BOX


MASTER PL-T Xtra 4 Pin


Lifetime






Life Expectancy Diagram - MASTER PL-T Xtra 32W/830/4P 1CT/5X10BOX







Life Expectancy Diagram - MASTER PL-T Xtra 32W/830/4P 1CT/5X10BOX

Lumen Maintenance Diagram - MASTER PL-T Xtra 32W/830/4P 1CT/ 5X10BOX



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.