



MASTER PL-T 4 Pin



MASTER PL-T 18W/840/4P 1CT/5X10BOX

Energy saving compact fluorescent lamp. Compact long-arc low-pressure mercury discharge lamp. Envelope consists of 6 parallel narrow fluorescent tubes

Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- · Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information				
Cap base	GX24Q-2 [GX24q-2]			
Flux measurement reference	Sphere			
Light Technical				
Colour Code	840 [CCT of 4000K]			
Luminous Flux	1,150 lm			
Colour designation	Cool White (CW)			
Chromaticity Coordinate X (Nom)	0.38			
Chromaticity Coordinate Y (Nom)	0.38			
Correlated Colour Temperature	4000 K			
Luminous efficacy (rated) (min.)	67 lm/W			
Colour rendering index (CRI)	80			
Operating and Electrical				
Power Consumption	18.0 W			

Lamp current (nom.)	0.210 A			
Controls and Dimming				
Dimmable	Yes			
Approval and Application				
Energy Efficiency Class	G			
Mercury (Hg) content (max.)	1.4 mg			
Mercury (Hg) content (nom.)	1.4 mg			
Energy consumption kWh/1,000 hours	18 kWh			
EPREL registration number	423343			
Product Data				
Order product name	MASTER PL-T 18W/840/4P 1CT/5X10BOX			
Full product name	MASTER PL-T 18W/840/4P 1CT/5X10BOX			
Full EOC	871150061099770			
Order code	61099770			


Datasheet, 2023, April 15 data subject to change

MASTER PL-T 4 Pin

Material no. (12 NC)	927914484071			
Local order code	18PLT8404PINCS			
SAP numerator – quantity per pack	1			
EAN/UPC — Product/Case	8711500610997			


Numerator – packs per outer box	50
EAN/UPC - Case	8711500611017

Dimensional drawing




Product	D (max)	A (max)	B (max)	C (max)
MASTER PL-T 18W/840/4P 1CT/5X10BOX	41.0 mm	71.7 mm	96.0 mm	111.7 mm


Photometric data



Spectral Power Distribution Colour - MASTER PL-T 18W/840/4P 1CT/5X10BOX

Lifetime






Life Expectancy Diagram - MASTER PL-T 18W/840/4P 1CT/5X10BOX

Life Expectancy Diagram - MASTER PL-T 18W/840/4P 1CT/5X10BOX

MASTER PL-T 4 Pin

Lifetime



Lumen Maintenance Diagram - MASTER PL-T 18W/840/4P 1CT/5X10BOX



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.