

MASTER PL-T 2 Pin

MASTER PL-T 26W/840/2P 1CT/5X10BOX

Energy saving compact fluorescent lamp. Compact long-arc low-pressure mercury discharge lamp. Envelope consists of 6 parallel narrow fluorescent tubes

Warnings and Safety

- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	GX24D-3 [GX24d-3]
Flux measurement reference	Sphere
Life to 50% Failures (Nom)	10,000 hour(s)

Light Technical	
Color Code	840 [CCT of 4000K]
Luminous Flux	1,800 lm
Color Designation	Cool White (CW)
Chromaticity Coordinate X (Nom)	0.38
Chromaticity Coordinate Y (Nom)	0.38
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (Rated) (Min)	66 lm/W
Color rendering index (CRI)	80

Operating and Electrical	
Power Consumption	26.9 W
Lamp Current (Nom)	0.335 A

Controls and Dimming	
Dimmable	No

Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) Content (Max)	1.4 mg
Mercury (Hg) Content (Nom)	1.4 mg
Energy Consumption kWh/1000 h	27 kWh
EPREL Registration Number	423345


Product Data	
Order product name	MASTER PL-T 26W/840/2P 1CT/5X10BOX

MASTER PL-T 2 Pin

Full product name	MASTER PL-T 26W/840/2P 1CT/5X10BOX
Full product code	871150061113070
Order code	927914584071
Material Nr. (12NC)	927914584071
Local order code	PLT26W8402PM
Numerator - Quantity Per Pack	1


EAN/UPC - Product/Case	8711500611130
Numerator - Packs per outer box	50
EAN/UPC - Case	8711500611161

Dimensional drawing




Product	D (max)	A (max)	B (max)	C (max)
MASTER PL-T 26W/840/2P 1CT/5X10BOX	41 mm	86.7 mm	111.0 mm	134.2 mm

Photometric data




Spectral Power Distribution Colour - MASTER PL-T 26W/840/2P 1CT/5X10BOX

Lifetime




Life Expectancy Diagram - MASTER PL-T 26W/840/2P 1CT/5X10BOX



Life Expectancy Diagram - MASTER PL-T 26W/840/2P 1CT/5X10BOX

MASTER PL-T 2 Pin

Lifetime



Lumen Maintenance Diagram - MASTER PL-T 26W/840/2P 1CT/5X10BOX

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.