



MASTER TL-D Super 80



MASTER TL-D Super 80 30W/827 SLV/25

The MASTER TL-D Super 80 lamp offers more lumens per watt and better color rendering than TL-D standard colors. Furthermore, it has a lower mercury content. The lamp can be operated in existing TL-D luminaires.

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information					
Cap-Base	G13 [Medium Bi-Pin Fluorescent]				
Flux measurement reference	Sphere				
Life to 50% Failures (Nom)	15,000 hour(s)				
Light Technical					
Color Code	827 [CCT of 2700K]				
Luminous Flux	2,400 lm				
Color Designation	Incandescent White				
Chromaticity Coordinate X (Nom)	0.463				
Chromaticity Coordinate Y (Nom)	0.42				
Correlated Color Temperature (Nom)	2700 K				
Luminous Efficacy (rated) (Nom)	80 lm/W				
Color rendering index (CRI)	82				
Operating and Electrical					
Power Consumption	30.2 W				

Lamp Current (Nom)	0.360 A				
Controls and Dimming					
Dimmable	Yes				
Mechanical and Housing					
Bulb Shape	Т8				
Approval and Application					
Energy Efficiency Class	G				
Mercury (Hg) Content (Nom)	1.7 mg				
Energy Consumption kWh/1000 h	31 kWh				
EPREL Registration Number	423370				
Product Data					
Order product name	MASTER TL-D Super 80 30W/827 SLV/25				
Full product name	MASTER TL-D Super 80 30W/827 SLV/25				


Datasheet, 2024, February 23 data subject to change

MASTER TL-D Super 80

Full product code	871150063180040
Order code	927920582723
Material Nr. (12NC)	927920582723
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500631800


Numerator - Packs per outer box	25
EAN/UPC - Case	8711500631817

Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL-D Super 80	28 mm	894.6 mm	901.7 mm	899.3 mm	908.8 mm
30W/827 SLV/25					


Photometric data



Spectral Power Distribution Colour - MASTER TL-D Super 80 30W/827 SLV/25

Lifetime






Life Expectancy Diagram - MASTER TL-D Super 80 30W/827 SLV/25

Life Expectancy Diagram - MASTER TL-D Super 80 30W/827 SLV/25

MASTER TL-D Super 80

Lifetime



Lumen Maintenance Diagram - MASTER TL-D Super 80 30W/827 SLV/25



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.