



MASTER TL-D Super 80

MASTER TL-D Super 80 36W/835 1SL/25

The MASTER TL-D Super 80 lamp offers more lumens per watt and better color rendering than TL-D standard colors. Furthermore, it has a lower mercury content. The lamp can be operated in existing TL-D luminaires.

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information				
Cap-Base	G13 [Medium Bi-Pin Fluorescent]			
Flux measurement reference	Sphere			
Life to 50% Failures (Nom)	15,000 hour(s)			
Light Technical				
Color Code	835 [CCT of 3500K]			
Luminous Flux	3,350 lm			
Color Designation	White (WH)			
Chromaticity Coordinate X (Nom)	0.409			
Chromaticity Coordinate Y (Nom)	0.394			
Correlated Color Temperature (Nom)	3500 K			
Luminous Efficacy (rated) (Nom)	93 lm/W			
Color rendering index (CRI)	82			
Operating and Electrical				
Power Consumption	36.8 W			
	·			

Lamp Current (Nom)	0.440 A			
Controls and Dimming				
Dimmable	Yes			
Mechanical and Housing				
Bulb Shape	T8			
Approval and Application				
Energy Efficiency Class	G			
Mercury (Hg) Content (Nom)	1.7 mg			
Energy Consumption kWh/1000 h	37 kWh			
EPREL Registration Number	423381			
Product Data				
Order product name	MASTER TL-D Super 80 36W/835 1SL/25			
Full product name	MASTER TL-D Super 80 36W/835 1SL/25			


Datasheet, 2023, May 8 data subject to change

MASTER TL-D Super 80

Full product code	871150063198540
Order code	63198540
Material Nr. (12NC)	927921083523
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500631985


Numerator - Packs per outer box	25
EAN/UPC - Case	8711500631992

Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL-D Super 80	28 mm	1,199.4 mm	1,206.5 mm	1,204.1 mm	1,213.6 mm
36W/835 1SL/25					


Photometric data



Spectral Power Distribution Colour - MASTER TL-D Super 80 36W/835 1SL/25

Lifetime






Life Expectancy Diagram - MASTER TL-D Super 80 36W/835 1SL/25

Life Expectancy Diagram - MASTER TL-D Super 80 36W/835 1SL/25

MASTER TL-D Super 80

Lifetime



Lumen Maintenance Diagram - MASTER TL-D Super 80 36W/835 1SL/25



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.