Lighting

PHILIPS

G A G

MASTER TL-D Super 80

MASTER TL-D Super 80 70W/840 1SL/25

Low-pressure mercury discharge lamps with a tubular 26 mm envelope

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Product data

General Information		Controls and Dimming		
Cap-Base	G13 [Medium Bi-Pin Fluorescent]	Dimmable	Yes	
Flux measurement reference	Sphere			
Life to 50% Failures (Nom)	15,000 hour(s)	Mechanical and Housing		
		Bulb Shape	Т8	
Light Technical				
Color Code	840 [CCT of 4000K]	Approval and Application		
Luminous Flux	6,200 lm	Energy Efficiency Class	G	
Color Designation	Cool White (CW)	Mercury (Hg) Content (Max)	3 mg	
Chromaticity Coordinate X (Nom)	0.38	Mercury (Hg) Content (Nom)	3.0 mg	
Chromaticity Coordinate Y (Nom)	0.38	Energy Consumption kWh/1000 h	70 kWh	
Correlated Color Temperature (Nom)	4000 K	EPREL Registration Number	423436	
Luminous Efficacy (rated) (Nom)	89 lm/W			
Color rendering index (CRI)	81	Product Data		
		Order product name	MASTER TL-D Super 80 70W/840 SLV/25	
Operating and Electrical		Full product name	MASTER TL-D Super 80 70W/840 1SL/25	
Power Consumption	70.0 W	Full product code	871150061592340	
Lamp Current (Nom)	0.690 A	Order code	61592340	
		Material Nr. (12NC)	927923884014	

MASTER TL-D Super 80


Numerator - Quantity Per Pack	1	EAN/UPC - Case	8711500615930
EAN/UPC - Product/Case	8711500615923		
Numerator - Packs per outer box	25		

Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL-D Super 80	28 mm	1,763.8 mm	1,770.9 mm	1,768.5 mm	1,778 mm
70W/840 SLV/25					

Photometric data




Spectral Power Distribution Colour - MASTER TL-D Super 80 70W/840 SLV/25

Lifetime




Life Expectancy Diagram - MASTER TL-D Super 80 70W/840 SLV/25



Life Expectancy Diagram - MASTER TL-D Super 80 70W/840 SLV/25

MASTER TL-D Super 80

Lifetime



Lumen Maintenance Diagram - MASTER TL-D Super 80 70W/840 SLV/25



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, May 8 - data subject to change