PHILIPS

Lighting



MASTER TL5 高效率

MASTER TL5 HE 14W/840 SLV/40

直径 16 毫米的荧光灯

安全提示

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

产品数据

一般信息	
底盖	G5 [G5]
功能	na [Not Applicable]
光通量测量参考	Sphere

灯技术	
颜色代码	840 [CCT of 4000K]
光通量	1,200 lm
颜色名称	冷白色 (CW)
色度坐标 X (标称)	0.38
色度坐标 Y (标称)	0.38
相关色温 (标称)	4000 K
光效 (额定)(标称)	86 lm/W
显色指数 (CRI)	80

操作和电气	
功耗	14.0 W
灯具电流 (标称)	0.165 A

控制和调光	
可调光	是

机械和外壳	
灯泡外形	T5 [16 毫米 (T5)]


审批和申请	
能效等级	G
汞 (Hg) 含量 (标称)	1.2 mg
能耗 kWh/1000 h	14 kWh
EPREL 注册号	423447

产品数据	
订单产品名称	MASTER TL5 HE 14W/840 SLV/40
完整的产品名称	MASTER TL5 HE 14W/840 SLV/40
完整产品代码	871150063940055
订购代码	927926084055
材料编号 (12NC)	927926084055
计算器 - 每包数量	1
EAN/UPC - 产品/箱	8711500639400
计算器 - 每个外包装箱中的包数	40

MASTER TL5 高效率


EAN/UPC - 案例	8711500867483

二维绘图




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HE 14W/840 SLV/40	17 mm	549.0 mm	556.1 mm	553.7 mm	563.2 mm

光度数据




Spectral Power Distribution Colour - MASTER TL5 HE 14W/840 SLV/40

寿命



Life Expectancy Diagram - MASTER TL5 HE 14W/840 SLV/40



Life Expectancy Diagram - MASTER TL5 HE 14W/840 SLV/40

MASTER TL5 高效率

寿命



Lumen Maintenance Diagram - MASTER TL5 HE 14W/840 SLV/40

© 2023 Signify Holding 保留所有权利。 Signify 对此文档所包含信息的准确性或完整性不作任何陈述或保证，也不对根据此文档信息做出的任何行为负责。 本文档中提供的信息不作为任何商业要约，也不构成任何报价或合同的一部分，除非 Signify 同意。
Philips 和 Philips Shield Emblem 是 Koninklijke Philips N.V. 的注册商标。